



LINEA: Dial thermostat 100-240V 2M canvas white

30440.C

Wiring devices / Traditional wiring devices / LINEA / Devices

Dial thermostat 100-240V 2M canvas white

Dial thermostat with relay output 5(2) A 240 V~, heating and air conditioning in ON/OFF MODE, class I temperature control device (contribution 1%), white LED backlighting with brightness control, 100-240 V 50/60 Hz power supply, to be completed with cover plate, canvas - 2 modules

- Simple programming
- Suitable for all heating or cooling systems
- Maximum simplicity thanks to the large knob
- Hotkeys are designed for quick interaction



Product Status

3 - Active


Minimum order quantity

1 NR


Sheets, Manuals, Documentation

- [Light Multilanguage instructions sheet \(625 kb\)](#)
- [Full Multilanguage instructions sheet \(1398 kb\)](#)


Drawings



Space view



Backside view



3D View

Technical data

- **Class group:** Stats, switches and controllers
- **Class:** Room thermostat
- **Model:** On/Off
- **Type of power supply:** 230 V AC
- **Connection:** 2-wire
- **With receiver:** No
- **Measuring range:** 0 - 40 °C
- **External sensor:** No
- **Thermal feedback:** Parallel
- **Control characteristic:** Other
- **Suitable for heating:** Yes
- **Number of heater outputs:** 1
- **Suitable for cooling:** Yes
- **Number of cooler outputs:** 1
- **Differential value:** 0,30 - 0,31 k
- **Adjustable differential:** No
- **Temperature readable:** Yes
- **With sound indicator:** No
- **Sensor/feeler type:** Resistance sensor
- **Mounting method:** Flush-mounted
- **Number of modules (module system):** 2
- **With display:** Yes
- **Operation:** Turn
- **With tap water circuit:** No
- **Contact type:** Normally open contact (NO)
- **Max. contact voltage:** 230 V
- **Max. contact load:** 5 A
- **Degree of protection (IP):** IP20
- **Degree of protection (NEMA):** Other
- **Explosion-proof:** No
- **Colour:** Beige
- **RAL-number:** 7032
- **Height:** 52,80 mm
- **Width:** 44,80 mm
- **Depth:** 41,70 mm
- **Diameter:** 0 mm
- **Class of the temperature control:** I
- **Compatible with Apple HomeKit:** No
- **Compatible with Google Assistant:** No
- **Compatible with Amazon Alexa:** No
- **IFTTT support available:** No

Certifications

- 00. CE Marking - EU
- 00. CE Marking - EU
- 37. Marking - Morocco
- 43. UKCA mark - Great Britain
- 99. WEEE Directive ([download](#))

Packaging



Code 8007352695603
Quantity 1 NR
Dim. 6x5.4x5.2 [cm]
Weight 69.2 [g]



Code 8007352695610
Quantity 10 NR
Dim. 28.1x13.1x6 [cm]
Weight 780.2 [g]



Code 8007352695627
Quantity 120 NR
Dim. 40x30x27 [cm]
Weight 9,839 [g]

Legal

Vimar reserves the right to change at any time and without notice the characteristics of the products reported. Installation should be carried out by qualified staff in compliance with the current regulations regarding the installation of electrical equipment in the country where the products are installed. For the terms of use of the information on the product info sheet see [Conditions of Use](#).