



LINEA: 16A IoT connected actuator white

30803.B

Wiring devices / View Wireless wiring devices / LINEA / Devices

16A IoT connected actuator white

VIEW Wireless electronic control device with NO 16 A 100-240 V~ relay output, local control with push button or remote control, double IoT technology on Bluetooth 5.0 standard for the creation of VIEW Wireless mesh system and on Zigbee 3.0 standard, function for measuring the instant power and energy consumed and load cut-off threshold, RGB LED visible in darkness with brightness control, 100-240 V 50/60 Hz power supply, white

- Compatible with SmartThings hub



Product Status

3 - Active

Minimum order quantity

1 NR

You may also be interested in




[30807.B - IoT connected Gateway 2M white](#)

Sheets, Manuals, Documentation

- [Light Multilanguage instructions sheet \(1031 kb\)](#)
- [Foglio istruzioni Full \(550 kb\)](#)
- [Feuille d'instructions Full \(548 kb\)](#)
- [Hoja de instrucciones Full \(546 kb\)](#)
- [Full instructions sheet \(544 kb\)](#)
- [Φυλλάδιο οδηγιών Full \(720 kb\)](#)
- [Anweisungsblatt Full \(547 kb\)](#)
- [Full \(610 kb\)](#)
- [Manuale app View Wireless \(15556 kb\)](#)
- [Manuel appli View Wireless \(37703 kb\)](#)
- [Manual app View Wireless \(37528 kb\)](#)
- [Manual View Wireless app \(37579 kb\)](#)
- [Εγχειρίδιο τεχνικού εγκατάστασης \(37781 kb\)](#)
- [Installationsanleitung View Wireless \(37508 kb\)](#)


Drawings



Space view



Backside view



3D View

Technical data

- **Class group:** Installation bus systems
- **Class:** Switch actuator for bus system
- **Bus system KNX:** No
- **Bus system KNX-RF (Radio Frequent):** No
- **Bus system radio frequent:** Yes
- **Bus system LON:** No
- **Bus system Powernet:** No
- **Other bus systems:** None
- **Radio frequent bidirectional:** No
- **Mounting method:** Flush-mounted
- **Width in number of modular spacings:** 1
- **Local operation/hand operation:** No
- **With LED indication:** Yes
- **Number of digital inputs:** 0
- **Suitable for C-load:** Yes
- **Max. number of switching contacts:** 1
- **Max. switching current:** 16 A
- **Rated current:** 16 A
- **Rated operating voltage:** 100,00 - 240,00 V
- **Different phases connectable:** No
- **With bus connection:** Yes
- **Bus module detachable:** No
- **Modular expandability:** No
- **Degree of protection (IP):** IP40

Certifications

- 00. CE Marking - EU
- 00. CE Marking - EU
- 01. IMQ - Italy ([download](#))
- 37. Marking - Morocco
- 40. Bluetooth technology
- 42. Zigbee certified
- 43. UKCA mark - Great Britain
- 46. UK PSTI compliance ([download](#))
- 99. WEEE Directive ([download](#))

Packaging



Code 8007352690110
Quantity 1 NR
Dim. 6x4.5x5.4 [cm]
Weight 56.96 [g]

Code 8007352744882
Quantity 72 NR
Dim. 37.5x30x13.5 [cm]
Weight 4,504.75 [g]

Legal

Vimar reserves the right to change at any time and without notice the characteristics of the products reported. Installation should be carried out by qualified staff in compliance with the current regulations regarding the installation of electrical equipment in the country where the products are installed. For the terms of use of the information on the product info sheet see [Conditions of Use](#).