



AHD: Video transducer Balun+power supp.2ch.2p

46862.B01

Safety / ELVOX CCTV / AHD / Accessories

Video transducer Balun+power supp.2ch.2p

Pair of Balun video passive transducers (transmitter/receiver) for video transmission on twisted pair, BNC connector for the video, jack for the power supply, cable connection with RJ45 connector, maximum distance attainable with CAT5 cable 50 m, compatible with PAL/NSC/SECAM, built-in electrostatic discharge protection



Product Status

3 - Active

Minimum order quantity

1 NR

Sheets, Manuals, Documentation

• Multilanguage instructions sheet (661 kb)

Technical data

- Class group: Data and telecommunication
- Class: Balun
- Application: Other
- **Connection 1**: BNC
- Connection type connection 1: Plug
- Impedance connection 1: 75 Ohm
- Pin assignment connection 1: Other

Certifications

00. CE Marking - EU

Connection 2: Other

- Connection type connection 2: Plug
- Impedance connection 2: 100 Ohm
- Pin assignment connection 2: Other
- Screened: Yes
- Compatible with Grade2TV according to XP-C 90-483: No
- **Compatible with Grade3TV according to XP-C 90-483**: No

99. WEEE Directive (download)



 Code
 8013406261038

 Quantity
 1 NR

 Dim.
 8.4x8x3.8 [cm]

 Weight
 72.5 [g]

Legal

Vimar reserves the right to change at any time and without notice the characteristics of the products reported.Installation should be carried out by qualified staff in compliance with the current regulations regarding the installation of electrical equipment in the country where the products are installed.For the terms of use of the information on the product info sheet see Conditions of Use.