



## Shared A/V components: 2F+ LSZH cable 2x1 ext. laying Eca 500m

---

### 732I.E.500

ELVOX Door entry system / 2F/2F+ video door entry system / Shared A/V components / A/V cables

### 2F+ LSZH cable 2x1 ext. laying Eca 500m

Due Fili Plus cable for internal/external laying, 2x1 mm<sup>2</sup> twisted conductors, LSZH sheath and insulation, operating temperature -25/+70°C, 600/1000 V insulation, suitable for laying underground in dry ducting or channels with efficient drainage (max. 24 hrs wet), not suitable for laying directly underground, suitable for installation with category 1 energy cable (U0 = 400 V), green - 500 m reel



### Product Status

3 - Active

### Minimum order quantity

500 M


## Technical data

- **Class group:** Communication technique
- **Class:** Accessories/spare parts for door communication
- **Suitable for:** Outdoor station
- **Mounting method:** Flush-mounted
- **Material:** Other
- **Colour:** Green


## Certifications

- 00. CE Marking - EU ([download](#))
- 00. CE Marking - EU ([download](#))
- 43. UKCA mark - Great Britain

# Packaging



**Code** 8013406301246  
**Quantity** 1 M  
**Dim.** 100x0.3x0.3 [cm]  
**Weight** 76.8 [g]



**Code** 8013406301253  
**Quantity** 500 M  
**Dim.** 40x40x32 [cm]  
**Weight** 37,430 [g]

# Legal

Vimar reserves the right to change at any time and without notice the characteristics of the products reported. Installation should be carried out by qualified staff in compliance with the current regulations regarding the installation of electrical equipment in the country where the products are installed. For the terms of use of the information on the product info sheet see [Conditions of Use](#).