



Motors: HIDDY200D undergr. operator 24V 2m 200kg

EIM1

Safety / ELVOX Automations / Motors / Hinged

HIDDY200D undergr. operator 24V 2m 200kg

HIDDY 200D non-reversible 24 V electromechanical underground operator for swing gates with leaves up to 2 m and 200 kg, residential use, magnetic encoder, supplied with 2 m of cable



Product Status

3 - Active

Minimum order quantity

1 NR

Sheets, Manuals, Documentation

- [Esploso serie HIDDY 200D - EN \(70 kb\)](#)
- [Multilanguage installer manual \(6135 kb\)](#)

Technical data

- **Class group:** Gate operators, pumps and ventilators
- **Class:** Swing gate operator
- **Model:** One-wing, left and right
- **Max. width of door/gate wing:** 2.000 mm
- **Max. weight of door/gate leaf:** 200 kg
- **Type of current:** DC
- **Motor voltage:** 24 V
- **Limit switch:** Internal end switch
- **With motor control unit:** No
- **With post fittings:** No
- **With wing fittings:** No
- **With key-switch:** No
- **With radio receiver:** No

Certifications

- 00. CE Marking - EU
- 37. Marking - Morocco
- 99. WEEE Directive ([download](#))

Packaging



Code 8013406228192
Quantity 1 NR
Dim. 43.7x16x16 [cm]
Weight 8,184 [g]

Legal

Vimar reserves the right to change at any time and without notice the characteristics of the products reported. Installation should be carried out by qualified staff in compliance with the current regulations regarding the installation of electrical equipment in the country where the products are installed. For the terms of use of the information on the product info sheet see [Conditions of Use](#).