



Motors: HIDDY 350D underground operator 24V 3,5m

EIM2.24

Safety / ELVOX Automations / Motors / Hinged

HIDDY 350D underground operator 24V 3,5m

HIDDY 350D non-reversible 24 V electromechanical operator for underground installation for gate leaves up to 3.5 m and 200 kg, for tertiary and industrial use. Complete with 6 m of cable.



Product Status

3 - Active

Minimum order quantity

1 NR

Sheets, Manuals, Documentation

- [Installer manual \(2676 kb\)](#)

Technical data

- **Class group:** Gate operators, pumps and ventilators
- **Class:** Swing gate operator
- **Model:** 2 wings
- **Max. width of door/gate wing:** 3.500 mm
- **Max. weight of door/gate leaf:** 400 kg
- **Type of current:** DC
- **Motor voltage:** 24 V
- **Limit switch:** Gate stop
- **With motor control unit:** No
- **With post fittings:** No
- **With wing fittings:** No
- **With key-switch:** No
- **With radio receiver:** No

Certifications

- 00. CE Marking - EU
- 37. Marking - Morocco
- 43. UKCA mark - Great Britain
- 99. WEEE Directive ([download](#))

Packaging



Code 8013406305145
Quantity 1 NR
Dim. 27x35.5x19 [cm]
Weight 11,600 [g]

Legal

Vimar reserves the right to change at any time and without notice the characteristics of the products reported. Installation should be carried out by qualified staff in compliance with the current regulations regarding the installation of electrical equipment in the country where the products are installed. For the terms of use of the information on the product info sheet see [Conditions of Use](#).