



Motors: HIDDY350A undergr.operator 230V3.5m400kg

EIM2

Safety / ELVOX Automations / Motors / Hinged

HIDDY350A undergr.operator 230V3.5m400kg

HIDDY 350A non-reversible 230 V electromechanical underground operator for swing gates with leaves up to 3.5 m and 400 kg, tertiary and industrial use, supplied with 6 m of cable



Product Status

2 - Will be discontinued

Minimum order quantity

1 NR

Sheets, Manuals, Documentation

- [Installer manual \(3721 kb\)](#)

Technical data

- **Class group:** Gate operators, pumps and ventilators
- **Class:** Swing gate operator
- **Model:** One-wing, left and right
- **Max. width of door/gate wing:** 3.500 mm
- **Max. weight of door/gate leaf:** 800 kg
- **Type of current:** AC
- **Motor voltage:** 230 V
- **Limit switch:** Gate stop
- **With motor control unit:** No
- **With post fittings:** No
- **With wing fittings:** No
- **With key-switch:** No
- **With radio receiver:** No

Certifications

- 00. CE Marking - EU
- 37. Marking - Morocco
- 99. WEEE Directive ([download](#))

Packaging



Code 8013406228208
Quantity 1 NR
Dim. 27x35.5x19 [cm]
Weight 12,600 [g]

Legal

Vimar reserves the right to change at any time and without notice the characteristics of the products reported. Installation should be carried out by qualified staff in compliance with the current regulations regarding the installation of electrical equipment in the country where the products are installed. For the terms of use of the information on the product info sheet see [Conditions of Use](#).