



#### EV45ER/10

Safety / ELVOX Automations / Motors / Windows and doors

#### Radio tubular actuator 230Vac 10Nm

Ø45 mm tubular motor for roller shutters, 230 Vac, torque 10 Nm, rotation speed 15 rpm, absorbed power 112 W. With radio receiver and electronic limit switch incorporated in the motor. Residential, commercial and tertiary use, includes wall fixing bracket. Power cable length 2.5 m

#### **Product Status**

2 - Will be discontinued

Minimum order quantity

1 NR

#### Sheets, Manuals, Documentation

Installer manual (2016 kb)

### Technical data

- Class group: Gate operators, pumps and ventilators
- Class: Tube mounted motor
- Outer diameter: 45 mm
- Moment of torque: 10 N/m
- For roller blinds: Yes
- For awnings: No
- Max. weight of roller shutter: 20 kg

## Certifications

- 00. CE Marking EU
- 37. Marking Morocco

- **Type of end switch**: Electronic
- Back jump: No
- **Electronic route monitoring**: No
- Electronic obstacle recognition: No
- With carrier: Yes
- With shaft adapter: Yes
- Length: 625 mm
- 43. UKCA mark Great Britain
- 99. WEEE Directive (download)







# Legal

Vimar reserves the right to change at any time and without notice the characteristics of the products reported.Installation should be carried out by qualified staff in compliance with the current regulations regarding the installation of electrical equipment in the country where the products are installed.For the terms of use of the information on the product info sheet see Conditions of Use.