



Motors: Radio tubular actuator 230Vac 30Nm

EV45ER/30

Safety / ELVOX Automations / Motors / Windows and doors

Radio tubular actuator 230Vac 30Nm

Ø45 mm tubular motor for roller shutters, 230 Vac, torque 30 Nm, rotation speed 15 rpm, absorbed power 191 W. With radio receiver and electronic limit switch incorporated in the motor. Residential, commercial and tertiary use, includes wall fixing bracket. Power cable length 2.5 m.



Product Status

2 - Will be discontinued

Minimum order quantity

1 NR

Sheets, Manuals, Documentation

Installer manual (2016 kb)

Technical data

- Class group: Gate operators, pumps and ventilators
- **Class**: Tube mounted motor
- Outer diameter: 45 mm
- Moment of torque: 30 N/m
- For roller blinds: Yes
- For awnings: No
- Max. weight of roller shutter: 60 kg

- Type of end switch: Electronic
- Back jump: No
- Electronic route monitoring: No
- Electronic obstacle recognition: No
- With carrier: Yes
- With shaft adapter: Yes
- Length: 675 mm

Certifications

- 00. CE Marking EU
- 37. Marking Morocco

99. WEEE Directive (download)

Packaging



Code Quantity Dim.

8013406288530 1 NR

 Dim.
 73x8.5x8.5 [cm]

 Weight
 2,500 [g]



Code 8013406292865

Quantity 10 NR

Dim. 73x43x18.5 [cm] **Weight** 26,000 [g]

Legal

Vimar reserves the right to change at any time and without notice the characteristics of the products reported. Installation should be carried out by qualified staff in compliance with the current regulations regarding the installation of electrical equipment in the country where the products are installed. For the terms of use of the information on the product info sheet see Conditions of Use.