



Motors: Radio tubular actuator 230Vac 50Nm

EV45ER/50

Safety / ELVOX Automations / Motors / Windows and doors

Radio tubular actuator 230Vac 50Nm

Ø45 mm tubular motor for roller shutters, 230 Vac, torque 50 Nm, rotation speed 12 rpm, absorbed power 205 W. With radio receiver and electronic limit switch incorporated in the motor. Residential, commercial and tertiary use, includes wall fixing bracket. Power cable length 2.5 m



Product Status

2 - Will be discontinued

Minimum order quantity

1 NR

Sheets, Manuals, Documentation

Installer manual (2016 kb)

Technical data

- Class group: Gate operators, pumps and ventilators
- **Class**: Tube mounted motor
- Outer diameter: 45 mm
- Moment of torque: 50 N/m
- For roller blinds: Yes
- For awnings: No
- Max. weight of roller shutter: 95 kg

- Type of end switch: Electronic
- Back jump: No
- **Electronic route monitoring**: No
- Electronic obstacle recognition: No
- With carrier: Yes
- With shaft adapter: Yes
- Length: 675 mm

Certifications

- 00. CE Marking EU
- 37. Marking Morocco

- 43. UKCA mark Great Britain
- 99. WEEE Directive (download)

Packaging



Code Quantity Dim.

1 NR 73x8.5x8.5 [cm] 3,250 [g]

8013406288554



Code Support Quantity

8013406292889

uantity 10 NR

Dim. 73x43x18.5 [cm] **Weight** 33,000 [g]

Legal

Weight

Vimar reserves the right to change at any time and without notice the characteristics of the products reported. Installation should be carried out by qualified staff in compliance with the current regulations regarding the installation of electrical equipment in the country where the products are installed. For the terms of use of the information on the product info sheet see Conditions of Use.