



# Motors: Tubular rolling shutter motor 230V~ 40kg

#### EV45S40

Safety / ELVOX Automations / Motors / Windows and doors

#### Tubular rolling shutter motor 230V~ 40kg

230 V~ tubular motor for roller shutters, lifting capacity 40 kg, residential, commercial and tertiary use, 60 mm octagonal adaptors, complete with fixing brackets

- Complete with fixing brackets
- For use in the following sectors: residential, commercial and services
- Automations for roller shutters and sun awnings Every single roller shutter can be automated extremely simply, and can be controlled from a single point, usually positioned next to the roller shutter or incorporated into the home automation scenarios of the smart home
- IP 44 protection degree

#### **Product Status**

3 - Active

Minimum order quantity

1 NR

#### Sheets, Manuals, Documentation

Installer manual (10138 kb)



## Gallery



## Technical data

- Class group: Gate operators, pumps and ventilators
- Class: Tube mounted motor
- Outer diameter: 45 mm
- Moment of torque: 20 N/m
- For roller blinds: Yes
- For awnings: No
- Max. weight of roller shutter: 40 kg

## Certifications

- 00. CE Marking EU
- 43. UKCA mark Great Britain

# Packaging



8013406262448 Code Quantity 1 NR Dim. 51.5x8x8 [cm] Weight 2,465 [g]

Code Quantity Dim. Weight

8007352668362 4 NR 53.5x34x10 [cm] 9,860 [g]



- Back jump: No
- Electronic route monitoring: No
- Electronic obstacle recognition: No
- With carrier: Yes
- With shaft adapter: Yes
- Length: 494 mm
- 99. WEEE Directive (download)



Code 8013406304766 Quantity 5 NR Dim. Weight 12,800 [g]

53.5x44x10 [cm]

Legal

Vimar reserves the right to change at any time and without notice the characteristics of the products reported.Installation should be carried out by qualified staff in compliance with the current regulations regarding the installation of electrical equipment in the country where the products are installed.For the terms of use of the information on the product info sheet see Conditions of Use.