



Motors: Tubular rolling shutter motor 230V~ 95kg

EV45S95

Safety / ELVOX Automations / Motors / Windows and doors

Tubular rolling shutter motor 230V~ 95kg

230 V~ tubular motor for roller shutters, lifting capacity 95 kg, residential, commercial and tertiary use, 60 mm octagonal adaptors, complete with fixing brackets

- Complete with fixing brackets
- For use in the following sectors: residential, commercial and services
- Automations for roller shutters and sun awnings Every single roller shutter can be automated extremely simply, and can be controlled from a single point, usually positioned next to the roller shutter or incorporated into the home automation scenarios of the smart home
- . IP 44 protection degree

Product Status

3 - Active

Minimum order quantity

1 NR

Sheets, Manuals, Documentation

• Installer manual (10138 kb)



Gallery







Technical data

Class group: Gate operators, pumps and ventilators

Class: Tube mounted motor Outer diameter: 45 mm Moment of torque: 50 N/m

For roller blinds: Yes For awnings: No

Max. weight of roller shutter: 95 kg

Type of end switch: Mechanical

Back jump: No

Electronic route monitoring: No Electronic obstacle recognition: No

With carrier: Yes

With shaft adapter: Yes

Length: 564 mm

Certifications

00. CE Marking - EU

43. UKCA mark - Great Britain

99. WEEE Directive (download)

Packaging



Code Quantity Dim. Weight

8013406262462 1 NR 58.5x8x8 [cm] 3,071 [g]

Code 8007352668904 Quantity Dim. Weight

4 NR 58.5x34x10 [cm] 12,800 [g]



Code 8013406304780 Quantity 5 NR Dim.

58.5x44x10 [cm] Weight 16,000 [g]

Legal

Vimar reserves the right to change at any time and without notice the characteristics of the products reported. Installation should be carried out by qualified staff in compliance with the current regulations regarding the installation of electrical equipment in the country where the products are installed. For the terms of use of the information on the product info sheet see Conditions of Use.