



# Switchboards: IP55 surface consumer unit 24M+door grey

#### V51124

System infrastructure / Enclosures and control units / Switchboards / Surface mounting

#### IP55 surface consumer unit 24M+door grey

Surface mounting consumer unit with horizontally hinged transparent door, 24 modules, RAL 7035 grey. Adjustable DIN (60715 TH35) rail to accommodate non-standard products. Screwcaps for double insulation. Pre-set for support for earth terminal block V51856. It can be used with cable entry V51790 and adjoined to additional consumer units with joining accessories V51905 or V51912



#### **Product Status**

2 - Will be discontinued

### Minimum order quantity

1 NR

#### Sheets, Manuals, Documentation

Multilanguage instructions sheet (311 kb)

### Technical data

• Class group: Distribution boards

Class: Small distribution board

Mounting method: Surface mounted

Number of rows: 2

Width in number of modular spacings: 24

Type of covering: Door Cover model: Closed

Transparent cover/door: Yes

With lock: No

Housing material: PlasticBuilt-in depth: 0,00 mm

Inner depth: 139,00 mm

**DIN-rail**: Yes

• With mounting plate: No Extension possible: No

EMC-version: No Colour: Grey RAL-number: 0

Degree of protection (IP): IP55

Height: 375,00 mmWidth: 285,00 mmDepth: 140,00 mm

## Certifications

• 01. IMQ - Italy (download)

96. Electrotechnical expert (download)

# Packaging



Code 8007352078994 Quantity 1 NR

**Dim.** 28.5x37.5x14 [cm]

**Weight** 2,070 [g]



**Code** 8007352079007 **Quantity** 6 NR

quantity one

**Dim.** 46x60x40 [cm] **Weight** 13,699.33 [g]

070 [g]

## Legal

Vimar reserves the right to change at any time and without notice the characteristics of the products reported. Installation should be carried out by qualified staff in compliance with the current regulations regarding the installation of electrical equipment in the country where the products are installed. For the terms of use of the information on the product info sheet see Conditions of Use.