



# Connector block boxes: Flush mounting box 3M black

#### V71303.AU

System infrastructure / Enclosures and control units / Connector block boxes / Flush mounting

#### Flush mounting box 3M black

3-module flush mounting box, (Glow Wire 960 °C), for masonry walls, black

- Plenty of space of internal wiring
- Wide range of accessories available: anti-mortar covers, coupling joints to create multiple series of boxes
- Knockouts designed for the insertion of pipes with various crosssections
- Rack for fixing the dividing screen (patented)
- Fixing lug of the support screws with zinc-plating treatment to prevent the thread from clogging during installation and favour screwing



#### **Product Status**

3 - Active

#### Minimum order quantity

15 NR

# You may also be interested in



V71303 - Flush mounting box 3M light blue



V71633 - Flat cover 3M




V71323 - Antimortar cover for flush-mount box 3M





V71563 - Joint plate for flush-mount bixes yellow

## Drawings



Space view





Backside view

3D View

## Technical data

Class group: Connection material (electrotechnical)

Class: Box/housing for built-in mounting in the wall/ceiling

Mounting method: Flush-mounted

Shape: Rectangular

**Construction type**: Device connection box (round/square)

Model: Other

Provided with revolving ring: No

Couplable: Yes

**Equipped with**: None

• Diameter: 0 mm

**Length**: 59,00 mm

**Width**: 96,00 mm

**Depth**: 0,00 - 49,80 mm

Inner depth: 50,00 mm

For number of electric fittings: 3

Mounting switching equipment: Screwing

With screws: No

Housing feed-through by break-out opening: Yes

Housing feed-through by seal membrane: No

Housing feed-through by nozzle: No

Housing feed-through by step membrane: No

For tube diameter: 20/25 mm

Pipe locking: No

• Pipe locking optional: No Inlet from the rear: Yes

Number of inlets: 12

Number of included spouts: 0

Material: Plastic
Halogen free: Yes

Surface protection: Untreated

Colour: Black

Degree of protection (IP): IP00

Cover model: None
Transparent cover: No

**Cover attachment**: Screwed

Sealable: No

Circuit integrity: None

With screening: No

Air tight: No

• Max. conductor cross section: 0

Number of poles of the clamp: 0

**Clamp position fixed**: No

Luminaire hook mounting: No

• Nozzle: None

Special application: None

### Certifications

00. CE Marking - EU

01. IMQ - Italy (download)

43. UKCA mark - Great Britain

96. Electrotechnical expert (download)

# Packaging



Code Quantity Dim.

1 NR 10.6x7.4x5 [cm] 35.73 [g]

8007352080720



Code Quantity Dim.

8007352119437 15 NR 10.6x7.4x75 [cm] Weight 544.95 [g]



Code 8007352119468 Quantity 300 NR Dim. 59x39x44 [cm] 11,892 [g] Weight

## Legal

Weight

Vimar reserves the right to change at any time and without notice the characteristics of the products reported. Installation should be carried out by qualified staff in compliance with the current regulations regarding the installation of electrical equipment in the country where the products are installed. For the terms of use of the information on the product info sheet see Conditions of Use.