



Connector block boxes: Flush mounting box 4M light blue

V71304

System infrastructure / Enclosures and control units / Connector block boxes / Flush mounting

Flush mounting box 4M light blue

4-module flush mounting box, (Glow Wire 650 °C), for masonry walls, light blue

- Plenty of space of internal wiring
- Wide range of accessories available: anti-mortar covers, coupling joints to create multiple series of boxes
- Knockouts designed for the insertion of pipes with various crosssections
- Rack for fixing the dividing screen (patented)
- Fixing lug of the support screws with zinc-plating treatment to prevent the thread from clogging during installation and favour screwing

Product Status

3 - Active

Minimum order quantity

6 NR

You may also be interested in









box 4M black


V71304.AU - Flush mounting V71324 - Antimortar cover for flush-mount box 4M

V71634 - Flat cover 4M


V71550 - Dividing screen for flush-mount box yell



Drawings







Space view

Backside view

3D View

Technical data

Class group: Connection material (electrotechnical)

Class: Box/housing for built-in mounting in the wall/ceiling

Mounting method: Flush-mounted

Shape: Rectangular

Construction type: Device connection box (round/square)

Model: Other

Provided with revolving ring: No

Couplable: Yes Equipped with: None Diameter: 0 mm **Length**: 59,00 mm

Width: 121,00 mm Depth: 0,00 - 49,80 mm Inner depth: 50,00 mm

For number of electric fittings: 4

Mounting switching equipment: Screwing

With screws: No

Housing feed-through by break-out opening: Yes

Housing feed-through by seal membrane: No

Housing feed-through by nozzle: No

Housing feed-through by step membrane: No

For tube diameter: 20/25 mm

Pipe locking: No

Pipe locking optional: No

Inlet from the rear: Yes

Number of inlets: 14

Number of included spouts: 0

Material: Plastic Halogen free: Yes

Surface protection: Untreated

Colour: Blue

Degree of protection (IP): IP00

Cover model: None Transparent cover: No Cover attachment: Screwed

Sealable: No

Circuit integrity: None

With screening: No

Air tight: No

Max. conductor cross section: 0 Number of poles of the clamp: 0

Clamp position fixed: No

Luminaire hook mounting: No

Nozzle: None

Special application: None

Certifications

00. CE Marking - EU

01. IMQ - Italy (download)

15. CCC - China (download)

43. UKCA mark - Great Britain

50. Product Environm. Profile

96. Electrotechnical expert (download)

Packaging



Code Quantity Dim. Weight

8007352079403

1 NR 13.1x6.9x5 [cm] 38.2 [g]



Code Quantity Dim.

8007352079410 6 NR 13.1x6.9x30 [cm] Weight 238.27 [g]



Code Quantity Dim. Weight

96 NR 59.5x38.5x26.5 [cm] 4,595.33 [g]

8007352079427



Code Quantity Dim. Weight

8007352356245 2.304 NR 80x120x180 [cm] 115,000 [g]

Legal

Vimar reserves the right to change at any time and without notice the characteristics of the products reported. Installation should be carried out by qualified staff in compliance with the current regulations regarding the installation of electrical equipment in the country where the products are installed. For the terms of use of the information on the product info sheet see Conditions of Use.