



Connector block boxes: Flush mounting box 6-7M light blue

V71306

System infrastructure / Enclosures and control units / Connector block boxes / Flush mounting

Flush mounting box 6-7M light blue

6-7-module flush mounting box (GW 650 °C), for masonry walls, light blue

- Plenty of space of internal wiring
- Knockouts designed for the insertion of pipes with various crosssections
- Rack for fixing the dividing screen (patented)
- Fixing lug of the support screws with zinc-plating treatment to prevent the thread from clogging during installation and favour screwing
- Accessories available: anti-mortar covers and coupling joints to create multiple series of boxes



Product Status

3 - Active

Minimum order quantity

6 NR

You may also be interested in










box 6-7M black

for flush-mount box 6M


V71306.AU - Flush mounting V71326 - Antimortar cover V71550 - Dividing screen for flush-mount box yell

V71563 - Joint plate for flush-mount bixes yellow

Drawings







Space view Backside view

3D View

Technical data

Class group: Connection material (electrotechnical)

Class: Box/housing for built-in mounting in the wall/ceiling

Mounting method: Flush-mounted

Shape: Rectangular

Construction type: Device connection box (round/square)

Model: Other

Provided with revolving ring: No

Couplable: Yes

Equipped with: None

Diameter: 0 mm

Length: 59,00 mm

• Width: 174,00 mm

Depth: 0,00 - 49,60 mm

Inner depth: 50,00 mm

For number of electric fittings: 7

Mounting switching equipment: Screwing

With screws: No

A Housing feed-through by break-out opening: Yes

Housing feed-through by seal membrane: No

Housing feed-through by nozzle: No

Housing feed-through by step membrane: No

For tube diameter: 20/25 mm

Pipe locking: No

Pipe locking optional: No

Inlet from the rear: Yes

Number of inlets: 9

Number of included spouts: 0

Material: Plastic

• Halogen free: Yes

Surface protection: Untreated

Colour: Blue

Degree of protection (IP): IP00

Cover model: None
Transparent cover: No

Cover attachment: Screwed

Sealable: No

• Circuit integrity: None

With screening: No

Air tight: No

Max. conductor cross section: 0

Number of poles of the clamp: 0

Clamp position fixed: No

Luminaire hook mounting: No

Nozzle: None

Special application: None

Certifications

00. CE Marking - EU

01. IMQ - Italy (download)

15. CCC - China (download)

43. UKCA mark - Great Britain

96. Electrotechnical expert (download)

Packaging



Code Quantity Dim.

8007352079526 1 NR 18.4x9x5 [cm]

60 [g]

8007352079533

Code Quantity Dim.

6 NR 18.4x9x30 [cm] Weight 367.27 [g]

Code 8007352079540 Quantity 48 NR

Dim. 62x26x30 [cm] Weight 3,547.33 [g]

Legal

Weight

Vimar reserves the right to change at any time and without notice the characteristics of the products reported. Installation should be carried out by qualified staff in compliance with the current regulations regarding the installation of electrical equipment in the country where the products are installed. For the terms of use of the information on the product info sheet see Conditions of Use.