



Connector block boxes: Flush mounting box 6-7M light blue

V71306

System infrastructure / Enclosures and control units / Connector block boxes / Flush mounting

Flush mounting box 6-7M light blue

6-7-module flush mounting box (GW 650 °C), for masonry walls, light blue

- Plenty of space of internal wiring
- Knockouts designed for the insertion of pipes with various crosssections
- Rack for fixing the dividing screen (patented)
- Fixing lug of the support screws with zinc-plating treatment to prevent the thread from clogging during installation and favour screwing
- Accessories available: anti-mortar covers and coupling joints to create multiple series of boxes

Product Status

3 - Active

Minimum order quantity

6 NR

You may also be interested in










box 6-7M black

for flush-mount box 6M


V71306.AU - Flush mounting V71326 - Antimortar cover V71550 - Dividing screen for flush-mount box yell



Drawings







Space view

Backside view

3D View

Technical data

- Class group: Connection material (electrotechnical)
- Class: Box/housing for built-in mounting in the wall/ceiling
- Mounting method: Flush-mounted
- Shape: Rectangular
- **Construction type**: Device connection box (round/square)
- Model: Other
- Provided with revolving ring: No
- Couplable: Yes
- Equipped with: None
- Diameter: 0 mm
- Length: 59,00 mm
- Width: 174,00 mm
- **Depth**: 0,00 49,60 mm
- Inner depth: 50,00 mm
- For number of electric fittings: 7
- Mounting switching equipment: Screwing
- With screws: No
- Housing feed-through by break-out opening: Yes
- Housing feed-through by seal membrane: No
- Housing feed-through by nozzle: No
- Housing feed-through by step membrane: No
- For tube diameter: 20/25 mm
- Pipe locking: No

Certifications

- 00. CE Marking EU
- 01. IMQ Italy (download)
- 15. CCC China (download)

- Pipe locking optional: No
- Inlet from the rear: Yes
- Number of inlets: 9
- Number of included spouts: 0
- Material: Plastic
- Halogen free: Yes
- Surface protection: Untreated
- Colour: Blue
- Degree of protection (IP): IP00
- **Cover model**: None
- Transparent cover: No
- **Cover attachment**: Screwed
- Sealable: No
- Circuit integrity: None
- With screening: No
- Air tight: No
- Max. conductor cross section: 0
- Number of poles of the clamp: 0
- Clamp position fixed: No
- Luminaire hook mounting: No
- Nozzle: None
- Special application: None
- 43. UKCA mark Great Britain
- 96. Electrotechnical expert (download)



Legal

Vimar reserves the right to change at any time and without notice the characteristics of the products reported.Installation should be carried out by qualified staff in compliance with the current regulations regarding the installation of electrical equipment in the country where the products are installed.For the terms of use of the information on the product info sheet see Conditions of Use.