



# Connector block boxes: Flush mounting box 8M light blue

#### V71318

System infrastructure / Enclosures and control units / Connector block boxes / Flush mounting

#### Flush mounting box 8M light blue

8-module flush mounting box, (Glow Wire 650 °C), for masonry walls, light blue

- Plenty of space of internal wiring
- Wide range of accessories available: anti-mortar covers, coupling joints to create multiple series of boxes
- Knockouts designed for the insertion of pipes with various crosssections
- Rack for fixing the dividing screen (patented)
- Fixing lug of the support screws with zinc-plating treatment to prevent the thread from clogging during installation and favour screwing



#### **Product Status**

3 - Active

### Minimum order quantity

10 NR

## You may also be interested in




V71328 - Antimortar cover for flush-mount box 8M



V71631 - Antimortar flat profile cover 8(4+4)M


## **Drawings**



Space view



Backside view



3D View

#### Technical data

Class group: Connection material (electrotechnical)

Class: Box/housing for built-in mounting in the wall/ceiling

Mounting method: Flush-mounted

Shape: Rectangular

**Construction type**: Device connection box (round/square)

**Model**: Other

Provided with revolving ring: No

Couplable: Yes
Equipped with: None
Diameter: 0 mm
Length: 145,00 mm
Width: 124,50 mm
Depth: 0,00 - 56,80 mm
Inner depth: 50,00 mm

For number of electric fittings: 8

Mounting switching equipment: Screwing

With screws: No

Housing feed-through by break-out opening: Yes Housing feed-through by seal membrane: No

Housing feed-through by nozzle: No

Housing feed-through by step membrane: No

For tube diameter: 20/25 mm

Pipe locking: No

Pipe locking optional: No Inlet from the rear: Yes Number of inlets: 12

Number of included spouts: 0

Material: Plastic Halogen free: Yes

Surface protection: Untreated

Colour: Blue

Degree of protection (IP): IP00

Cover model: None Transparent cover: No Cover attachment: Screwed

Sealable: No

**Circuit integrity**: None **With screening**: No

Air tight: No

Max. conductor cross section: 0
Number of poles of the clamp: 0
Clamp position fixed: No

Luminaire hook mounting: No

Nozzle: None

Special application: None

### Certifications

00. CE Marking - EU

01. IMQ - Italy (download)

15. CCC - China (download)

43. UKCA mark - Great Britain

96. Electrotechnical expert (download)

# **Packaging**



Code Quantity Dim. Weight

8007352275492 1 NR 13.4x15.5x5.7 [cm] 80.53 [g]



Code Quantity Dim. Weight

8007352276642 10 NR 30.5x26x22 [cm] 1,175.33 [g]

# Legal

Vimar reserves the right to change at any time and without notice the characteristics of the products reported. Installation should be carried out by qualified staff in compliance with the current regulations regarding the installation of electrical equipment in the country where the products are installed. For the terms of use of the information on the product info sheet see Conditions of Use.