



Motors: Revers.rolling door gear motor 230V160kg

ZP08

Safety / ELVOX Automations / Motors / Windows and doors

Revers.rolling door gear motor 230V160kg

Reversible 230 V~ gear motor for rolling doors with 60 mm diameter shaft and 200 mm diameter spring box, lifting capacity 160 kg, residential and industrial use, facility for ZXP1 electromechanical brake, pair of adaptors for 48 mm diameter shaft and 220 mm diameter spring box, 4 metres of 4x1 mm² cable



Product Status

2 - Will be discontinued

Minimum order quantity

1 NR

Sheets, Manuals, Documentation

- [Installer manual \(953 kb\)](#)


Technical data

- **Class group:** Gate operators, pumps and ventilators
- **Class:** Tube mounted motor
- **Outer diameter:** 220 mm
- **Moment of torque:** 155 N/m
- **For roller blinds:** No
- **For awnings:** No
- **Max. weight of roller shutter:** 160 kg
- **Type of end switch:** Mechanical
- **Back jump:** No
- **Electronic route monitoring:** No
- **Electronic obstacle recognition:** No
- **With carrier:** Yes
- **With shaft adapter:** Yes
- **Length:** 460 mm

Certifications

- 00. CE Marking - EU
- 37. Marking - Morocco
- 43. UKCA mark - Great Britain
- 99. WEEE Directive ([download](#))

Packaging



Code 8013406191113
Quantity 1 NR
Dim. 41.3x23.5x24.5 [cm]
Weight 7,100 [g]

Legal

Vimar reserves the right to change at any time and without notice the characteristics of the products reported. Installation should be carried out by qualified staff in compliance with the current regulations regarding the installation of electrical equipment in the country where the products are installed. For the terms of use of the information on the product info sheet see [Conditions of Use](#).