



## Shared components: LED signalling unit 120V 0,2W green

### 00936.120.G

Wiring devices / Traditional wiring devices / Shared components /  
Accessories

#### LED signalling unit 120V 0,2W green

LED signalling unit 120 V 50/60 Hz 0,2 W, green. With incandescent or halogen lamps, the signalling unit has to be in-line with the charge (indicator unit OFF and controlled lamp ON), with other types of lamps the signalling unit has to be in parallel to the charge (indicator unit On and controlled lamp ON) or connected directly to the main power supply (indicator unit always ON)



3 - Active

50 NR

- **Class group:** Domestic switching devices
- **Class:** Illumination insert for domestic switching devices
- **Application:** Switch/push button
- **Lamp type:** LED
- **With light source:** Yes
- **Colour light source:** Green
- **Lamp holder:** Other
- **Nominal voltage:** 120,00 - 120,01 V

- 00. CE Marking - EU
- 29. QCERT - Colombia
- 37. Marking - Morocco
- 96. Electrotechnical expert ([download](#))
- 99. WEEE Directive ([download](#))



8007352556737  
1 NR  
0.7x15x0.7 [cm]  
3.94 [g]



8007352556744  
50 NR  
13.9x11.9x7.4 [cm]  
238.4 [g]



8007352725034  
1,000 NR  
38.5x29.5x25 [cm]  
4,768 [g]

Vimar