



Shared components: LED signalling unit 120V 0,2W red

00936.120.R

Wiring devices / Traditional wiring devices / Shared components /
Accessories

LED signalling unit 120V 0,2W red

LED signalling unit 120 V 50/60 Hz 0,2 W, red. With incandescent or halogen lamps, the signalling unit has to be in-line with the charge (indicator unit OFF and controlled lamp ON), with other types of lamps the signalling unit has to be in parallel to the charge (indicator unit On and controlled lamp ON) or connected directly to the main power supply (indicator unit always ON)



3 - Active

50 NR

- **Class group:** Domestic switching devices
- **Class:** Illumination insert for domestic switching devices
- **Application:** Switch/push button
- **Lamp type:** LED
- **With light source:** Yes
- **Colour light source:** Red
- **Lamp holder:** Other
- **Nominal voltage:** 120,00 - 120,01 V
- 00. CE Marking - EU
- 29. QCERT - Colombia
- 37. Marking - Morocco
- 96. Electrotechnical expert ([download](#))
- 99. WEEE Directive ([download](#))



8 007352556751

8007352556751
1 NR
0.7x15x0.7 [cm]
3.94 [g]



8 007352556768

8007352556768
50 NR
13.9x11.9x7.4 [cm]
238.4 [g]



8 007352725041

8007352725041
1,000 NR
38.5x29.5x25 [cm]
4,768 [g]

Vimar