



Shared components: Binary input 4-channel 120/230V KNX

01510

Smart systems&products / KNX / Shared components / DIN devices

Binary input 4-channel 120/230V KNX

4-channel digital input device, programmable for NO, NC and 120-230 V~ contacts, KNX standard, installation on DIN rail (60715 TH35), occupies 2 17,5 mm modules




3 - Active



1 NR

- [Multilanguage instructions sheet \(619 kb\)](#)
- [Manuale installatore \(659 kb\)](#)

- [DB_ComponentiAutomazione_KNX_01.16_20210920.zip](#)
- [DB_ComponentiAutomazione_KNX_01.19_20230331.zip](#)



3D

- **Class group:** Installation bus systems
- **Class:** I/O device for bus system
- **Bus system KNX:** Yes
- **Bus system KNX-RF (Radio Frequent):** No
- **Bus system radio frequent:** No
- **Bus system LON:** No
- **Bus system Powernet:** No
- **Width in number of modular spacings:** 2

- **With bus connection:** Yes
- **LED controlling:** No
- **With LED indication:** Yes
- **Local operation/hand operation:** Yes
- **Suitable for C-load:** Yes
- **With switch function:** No
- **External signal voltage necessary:** No
- **Different phases connectable:** Yes

- 00. CE Marking - EU
- 27. KNX ([download](#))
- 37. Marking - Morocco
- 43. UKCA mark - Great Britain

- 92. RoHS UAE
- 96. Electrotechnical expert ([download](#))
- 99. WEEE Directive ([download](#))



8007352383555
 1 NR
 14.2x6.7x5.9 [cm]
 109 [g]

Vimar