



Surface mounting components: Presence detector+luminosity sensor KNX

01529.1

Smart systems&products / KNX / Surface mounting components / Non-modular components

Presence detector+luminosity sensor KNX




360° IR presence detector for switching ON/OFF and control of lighting, heating, air conditioning, ventilation according to brightness and/or movement, 1 - 1000 Lux adjustable brightness range, KNX standard, ceiling installation, dimensions 91x91x45 mm



3 - Active

1 NR

- [Multilanguage instructions sheet \(558 kb\)](#)
- [Manuale installatore \(2232 kb\)](#)
- [Installer manual \(2156 kb\)](#)
- [DB_ComandoSupervisione_KNX_REL-01.17_20230117.zip](#)



3D

- **Class group:** Installation bus systems
- **Class:** Movement sensor for bus system
- **Bus system KNX:** Yes
- **Bus system KNX-RF (Radio Frequent):** No
- **Bus system radio frequent:** No
- **Bus system LON:** No
- **Bus system Powernet:** No
- **Radio frequent bidirectional:** No
- **Model:** Other
- **Mounting method:** Surface mounted
- **Material:** Plastic
- **Material quality:** Thermoplastic
- **Surface protection:** Untreated

- **Surface finishing:** Matt
- **Colour:** White
- **RAL-number (similar):** 9016
- **Transparent:** No
- **With bus connection:** Yes
- **Operation mode switch:** No
- **Staircase light controller:** No
- **Response value luminosity adjustable:** Yes
- **Teach-function for response value luminosity:** No
- **Switch-off delay self-learning:** Yes
- **Optimum mounting height:** 2,50 m
- **Max. reach sideways:** 16,00 m
- **Detection angle vertical:** 0 - 180

- 00. CE Marking - EU
- 27. KNX ([download](#))
- 37. Marking - Morocco

- 43. UKCA mark - Great Britain
- 99. WEEE Directive ([download](#))



8007352556485
 1 NR
 12x9.4x6 [cm]
 137 [g]

Vimar