



Shared components: Dimmer KNX 2 OUT200W LED 120-240V

01538

Smart systems&products / KNX / Shared components / DIN devices

Dimmer KNX 2 OUT200W LED 120-240V

Dimmer 120-240 V~ 50/60 Hz, phase-cutting, 2 outputs for incandescent lamps 40-300 W 240 V~, 20-150 W 120 V~, electronic transformers 40-200 VA, CFL lamps 10-200 W, LED lamps 10-200 W, push buttons for local control, KNX standard, protection fuse, installation on DIN rail (60715 TH35), occupies 4 modules size 17.5 mm





3 - Active

1 NR

- [Multilanguage instructions sheet \(1870 kb\)](#)
- [Manuale installatore \(1171 kb\)](#)
- [Installer manual \(844 kb\)](#)

- [DB_ComponentiAutomazione_KNX_01.16_20210920.zip](#)
- [DB_ComponentiAutomazione_KNX_01.19_20230331.zip](#)



3D

- **Class group:** Installation bus systems
- **Class:** Power supply for bus system
- **Bus system KNX-RF (Radio Frequent):** Yes

- **Bus system radio frequent:** No
- **Bus system LON:** No
- **Bus system Powernet:** No

- 00. CE Marking - EU
- 37. Marking - Morocco
- 43. UKCA mark - Great Britain

- 92. RoHS UAE
- 99. WEEE Directive ([download](#))



8007352613454
1 NR
11.7x10.8x7.1 [cm]
211.4 [g]

Vimar