



Surface mounting components: By-alarm - RF IR detector

01728

Safety / By-alarm Plus / Surface mounting components / Non-modular components




By-alarm - RF IR detector

By-alarm passive infrared presence detector, 868 MHz radio frequency connection, 1 input for external magnetic contact, powered by one 3 V CR123 battery (supplied)

2 - Will be discontinued

1 NR

- [Multilanguage instructions sheet \(1002 kb\)](#)
- [Anweisungsblatt \(626 kb\)](#)



3D

- **Class group:** Alarm installations, emergency call and signalling
- **Class:** Movement detector for danger detection system
- **Type of messaging:** Passive infrared
- **Mounting method:** Surface mounting
- **Detection range:** 98
- **Operating current:** 0,00 mA
- **Operating voltage:** 3,00 - 3,01 V

- **Height:** 111,00 mm
- **Width:** 60,80 mm
- **Depth:** 45,40 mm
- **Characteristic:** Distance
- **Cover monitoring:** Yes
- **Radio system:** Yes

- 00. CE Marking - EU
- 19. NOM - Mexico
- 37. Marking - Morocco
- 43. UKCA mark - Great Britain
- 99. WEEE Directive ([download](#))



8 0 0 7 3 5 2 5 4 8 0 2 2

8007352548022
1 NR
14.2x6.7x5.9 [cm]
136 [g]

Vimar