



Surface mounting components: By-alarm Plus RF mini magnetic contact

03834

Safety / By-alarm Plus / Surface mounting components / Non-modular components

By-alarm Plus RF mini magnetic contact




By-alarm Plus magnetic contact and shock/tilt sensor, 868 MHz radio frequency connection, power supply with 1 CR2 3V lithium battery, white

3 - Active

1 NR



- [Multilanguage instructions sheet \(866 kb\)](#)
- [Feuille d'instructions \(480 kb\)](#)
- [Anwendungshinweise \(481 kb\)](#)



3D

- **Class group:** Alarm installations, emergency call and signalling
- **Class:** Opening detector for danger detection system
- **Mounting method:** Surface mounting
- **Contacts:** 1 make contact (NO)
- **Wireless:** Yes
- **With connection cable:** No
- **Colour:** White
- **Sensor length:** 5.750,00 mm

- **Width sensor:** 3.500,00 mm
- **Height of sensor:** 2.270,00 mm
- **Compatible with Apple HomeKit:** No
- **Compatible with Google Assistant:** No
- **Compatible with Amazon Alexa:** No
- **IFTTT support available:** No
- **VdS class:** None

- 00. CE Marking - EU
- 21. IMQ-SICUREZZA - Italy
- 37. Marking - Morocco

- 43. UKCA mark - Great Britain
- 46. UK PSTI compliance ([download](#))
- 99. WEEE Directive ([download](#))



8007352708495
1 NR
6x5.4x5.3 [cm]
54.67 [g]



8007352708525
10 NR
28.1x13.1x6 [cm]
621.4 [g]



8007352708549
120 NR
38.5x29x30 [cm]
7,908 [g]

Vimar