



Surface mounting components: Connected magnetic contact

03980

Wiring devices / View Wireless wiring devices / Surface mounting components / Non-modular components

Connected magnetic contact

Connected magnetic contact for windows and doors, View Wireless, Bluetooth 5.0 standard technology for mesh system realization, 1 clean-contact input, powered with AA LR6 1,5 V batteries (not supplied), white. To use as accessory of connected thermostat or with gateway as sensor for notification of magnetic contact open/close






3 - Active

1 NR

- [Multilanguage instructions sheet \(789 kb\)](#)
- [Manuale app View Wireless \(15556 kb\)](#)
- [Manuel appli View Wireless \(37703 kb\)](#)
- [Manual app View Wireless \(37528 kb\)](#)
- [Manual View Wireless app \(37579 kb\)](#)
- [Εγχειρίδιο τεχνικού εγκατάστασης \(37781 kb\)](#)
- [Installationsanleitung View Wireless \(37508 kb\)](#)

- [App View Wireless - temperature control](#)




3D

- **Class group:** Alarm installations, emergency call and signalling
- **Class:** Opening detector for danger detection system

- **Mounting method:** Surface mounting
- **Colour:** Other

- 00. CE Marking - EU ([download](#))
- 06. SUBTEL - Chile
- 29. QCERT - Colombia
- 37. Marking - Morocco

- 40. Bluetooth technology
- 43. UKCA mark - Great Britain
- 92. RoHS UAE
- 99. WEEE Directive ([download](#))



8007352657564
1 NR
12.2x7.9x3.3 [cm]
152.8 [g]

Vimar