



8000: 1P 10AX 2-way switch

08285

Wiring devices / Traditional wiring devices / 8000 / Devices

1P 10AX 2-way switch

1P 10 AX 250 V~ 2-way switch (3 terminals), with directional arrows and central OFF position. Max 100 W for self-ballasted lamps (IEC 60669-1:2017)

3 - Active

50 NR



- **Class group:** Domestic switching devices
- **Class:** Push button
- **Assembly arrangement:** Modular device for domestic switching devices
- **Model:** Other
- **Method of operation:** Rocker
- **Number of rockers:** 1
- **Number of poles:** 1
- **Nominal voltage:** 250 V
- **Rated current:** 10,00 A
- **With lighting:** No
- **Feedback-signal contact:** No
- **Mounting method:** Flush-mounted
- **Type of fastening:** Engage (snap)
- **Material:** Plastic
- **Material quality:** Thermoplastic
- **Halogen free:** Yes
- **Surface protection:** Untreated
- **Surface finishing:** Matt
- **Colour:** White
- **RAL-number (similar):** 9001
- **Transparent:** No
- **Label space/information surface:** Yes
- **Suitable for degree of protection (IP):** IP40
- **Device height:** 45,00 mm
- **Device depth:** 43,00 mm
- 00. CE Marking - EU
- 01. IMQ - Italy ([download](#))
- 10. EAC Eurasian Customs Union
- 14. TSE - Turkey
- 37. Marking - Morocco
- 43. UKCA mark - Great Britain
- 96. Electrotechnical expert ([download](#))
- 99. WEEE Directive ([download](#))



8 007352014510

8007352014510
1 NR
5.1x2.8x5.3 [cm]
28.3 [g]



8 007352009264

8007352009264
50 NR
26.9x11.6x14.2 [cm]
1,510.53 [g]

Vimar