



## 8000: 2P 10AX 2-way switch

**08286**

Wiring devices / Traditional wiring devices / 8000 / Devices

### 2P 10AX 2-way switch

2P 10 AX 250 V~ 2-way switch (6 terminals), with directional arrows and central OFF position. Max 100 W for self-ballasted lamps (IEC 60669-1:2017)

3 - Active

50 NR



- **Class group:** Domestic switching devices
  - **Class:** Push button
  - **Assembly arrangement:** Modular device for domestic switching devices
  - **Model:** Other
  - **Method of operation:** Rocker
  - **Number of rockers:** 1
  - **Number of poles:** 2
  - **Nominal voltage:** 250 V
  - **Rated current:** 10,00 A
  - **With lighting:** No
  - **Feedback-signal contact:** No
  - **Mounting method:** Flush-mounted
  - **Type of fastening:** Engage (snap)
  - **Material:** Plastic
  - **Material quality:** Thermoplastic
  - **Halogen free:** Yes
  - **Surface protection:** Untreated
  - **Surface finishing:** Matt
  - **Colour:** White
  - **RAL-number (similar):** 9001
  - **Transparent:** No
  - **Label space/information surface:** Yes
  - **Suitable for degree of protection (IP):** IP40
  - **Device height:** 45,00 mm
  - **Device depth:** 43,00 mm
- 
- 00. CE Marking - EU
  - 01. IMQ - Italy ([download](#))
  - 10. EAC Eurasian Customs Union
  - 14. TSE - Turkey
  - 37. Marking - Morocco
  - 43. UKCA mark - Great Britain
  - 96. Electrotechnical expert ([download](#))
  - 99. WEEE Directive ([download](#))



8 007352014527

8007352014527  
1 NR  
5.1x2.8x5.3 [cm]  
37.82 [g]



8 007352009271

8007352009271  
50 NR  
26.9x11.6x14.2 [cm]  
2,014.2 [g]

Vimar