



## 8000: 2P+E 16A P30 outlet+C16 CB

---

### 08443

Wiring devices / Traditional wiring devices / 8000 / Devices

#### **2P+E 16A P30 outlet+C16 CB**

2P+E 16 A 250 V~ SICURY socket outlet, Italian standard P30 (lateral and central earth contacts) interlocked with 1P+N C 16 circuit breaker, supply voltage 230 V~ 50 Hz, breaking capacity 3000 A - 3 special modules



2 - Will be discontinued

5 NR

- **Class group:** Domestic switching devices
- **Class:** Socket outlet
- **Model:** Italian type P30
- **Number of units:** 2
- **Number of modules (module system):** 3
- **Number of socket outlets switchable:** 1
- **Imprint/indication:** None
- **Connection type:** Screwed terminal
- **With hinged lid:** No
- **With enhanced contact protection:** Yes
- **Label space/information surface:** Yes
- **Colour:** White
- **RAL-number (similar):** 9001
- **Metallic colour:** No
- **Transparent:** No
- **Lockable:** No
- **Eject-mechanism:** No
- **Insulated mounting:** No
- **With function lighting:** No
- **With orientation lighting:** No
- **Over voltage protection:** No
- **Fault current protection:** No
- **Special power supply:** No special power supply
- **Mounting method:** Flush-mounted
- **Type of fastening:** Snap mounting (engagement)
- **Material:** Plastic
- **Material quality:** Thermoplastic
- **Halogen free:** Yes
- **Surface protection:** Untreated
- **Surface finishing:** Matt
- **With loop through function:** No
- **With on/off switch:** Yes
- **Rotated central insert:** No
- **Nominal current:** 16 A
- **Nominal voltage:** 230 V
- **Frequency:** 50,00 - 60,00 HZ
- **Suitable for degree of protection (IP):** IP20
- **Device height:** 45,00 mm
- **Device depth:** 56,30 mm

- 00. CE Marking - EU
- 01. IMQ - Italy ([download](#))
- 37. Marking - Morocco
- 96. Electrotechnical expert ([download](#))
- 99. WEEE Directive ([download](#))



8007352112940  
1 NR  
5.2x5.7x7.6 [cm]  
121.4 [g]



8007352112957  
5 NR  
21.4x11.6x6 [cm]  
664.87 [g]