



NEVE UP: IoT connected radar sensor 1M carbon mat

09179.CM

Wiring devices / View Wireless wiring devices / NEVE UP / Devices




IoT connected radar sensor 1M carbon mat

3 - Active

1 NR



- [Light Multilanguage instructions sheet \(1270 kb\)](#)
- [Full \(1182 kb\)](#)
- [Foglio istruzioni Full \(1140 kb\)](#)
- [Notice technique Full \(1105 kb\)](#)
- [Ficha de instrucciones Full \(1134 kb\)](#)
- [Full instructions sheet \(1131 kb\)](#)
- [Φυλλάδιο οδηγιών Full \(1254 kb\)](#)
- [Anweisungsblatt Full \(1104 kb\)](#)
- [Manuel appli View Wireless \(37703 kb\)](#)
- [Manual app View Wireless \(37528 kb\)](#)
- [Manual View Wireless app \(37579 kb\)](#)
- [Εγχειρίδιο τεχνικού εγκατάστασης \(37781 kb\)](#)
- [Installationsanleitung View Wireless \(37508 kb\)](#)



3D

- **Class group:** Domestic switching devices
- **Class:** Movement sensor/presence detector complete
- **Model:** Movement sensor
- **Sensor type:** High frequency
- **With DALI interface:** No
- **Constant light control:** No
- **HVAC-control:** No
- **Forced switch on:** Yes
- **Forced switch off:** No
- **Animal zone:** Yes
- **Creep-under protection:** No
- **Networkable:** Yes
- **Scan angle:** 100
- **Optimum mounting height:** 1,00 m
- **Staircase light controller:** No
- **Bridging switch:** No
- **Max. reach sideways:** 7 m
- **Max. presence range:** 45 m²
- **Max. reach frontally:** 7 m
- **Diameter reach on floor:** 0 m
- **Suitable for wireless transmission:** Yes
- **Remote operation:** Yes
- **With remote control:** No
- **Response value sensitivity adjustable:** Yes
- **Response value luminosity adjustable:** No
- **With signal unit:** Yes
- **Teach-function for response value luminosity:** No
- **Dim function with dimmer basic element:** No
- **Mounting method:** Flush-mounted
- **Suitable for ceiling mounting:** No
- **Connection type:** Screwed terminal
- **Material:** Plastic
- **Material quality:** Thermoplastic
- **Halogen free:** Yes
- **Surface protection:** Lacquered

- **Surface finishing:** Matt
- **Anti-bacterial treatment:** No
- **Colour:** Anthracite
- **RAL-number (similar):** 7016
- **Transparent:** No
- **Degree of protection (IP):** IP40
- **Voltage type:** AC
- **Frequency:** 50 - 60 HZ
- **Min. switch-on time:** 70 s
- **Max. duty cycle:** 0 min
- **Switch-off delay:** 1.080 s
- **Switching-on delay:** 0 s
- **Detection angle horizontal:** 0 - 100
- **Max. switching power:** 12,00 W
- **Max. switching power LED:** 12 W
- **Suitable for C-load:** No
- **Temperature:** 10 - 40 °C
- **Number of switching zones:** 1
- **Max. starting current:** 0,00 A
- **Min. starting current:** 0 A
- **Control current:** 0 mA
- **Substation input:** No
- **With alarm function:** Yes
- **Width:** 22,30 mm
- **Height:** 47,00 mm
- **Depth:** 49,40 mm
- **Built-in width:** 22,30 mm
- **Built-in depth:** 39,90 mm
- **Built-in length:** 47,00 mm
- **Min. depth of built-in installation box:** 48 mm
- **Compatible with Apple HomeKit:** No
- **Compatible with Google Assistant:** No
- **Compatible with Amazon Alexa:** No
- **IFTTT support available:** No

- 00. CE Marking - EU
- 37. Marking - Morocco
- 40. Bluetooth technology
- 43. UKCA mark - Great Britain

- 46. UK PSTI compliance ([download](#))
- 96. Electrotechnical expert ([download](#))
- 99. WEEE Directive ([download](#))



8 007352732643

8007352732643
1 NR
5.2x3.5x5.3 [cm]
47 [g]



8 007352732650

8007352732650
10 NR
19x11.3x6.2 [cm]
528.4 [g]

Vimar