



## NEVE UP: Vertical badge switch 2M white

**09463**

Wiring devices / Traditional wiring devices / NEVE UP / Devices

### Vertical badge switch 2M white

Upright electronic badge switch, 4 A 250 V~ NO change-over relay output (NON SELV), 120-230 V~ 50-60 Hz power supply, pocket lighting to be visible in darkness, trimmer for regulating switch-off time after removing the card, white - 2 modules. Supplied without ISO card (badge)




3 - Active

1 NR




09470 - Dial thermostat 100-240V 2M white




09026.PLS - Button 1M +diffuser PLS symb.white




09026.DND - Button 1M +diffuser DND symb.white



09290 - Shaver supply unit 230V white



09465 - Vertical pocket badge switch white






09257 - 2P+E13ASICURY multistandard outlet white



09052 - 1P NO 10A cord-operated push white



09181 - IR relay-switch 230V white



3D

- **Class group:** Alarm installations, emergency call and signalling
- **Class:** Access control system
- **Standalone:** Yes
- **Networkable:** No
- **PC-binding:** No
- **Type of interface:** None
- **Reading strategy:** Data medium
- **Signalling:** None

- **Mounting method:** Flush-mounted
- **Operating voltage AC 50 Hz:** 250,00 - 250,01 V
- **Operating voltage AC 60 Hz:** 250,00 - 250,01 V
- **Colour:** White
- **Material:** Plastic
- **Width:** 59,00 mm
- **Height:** 47,00 mm
- **Depth:** 43,50 mm

- 00. CE Marking - EU
- 37. Marking - Morocco

- 43. UKCA mark - Great Britain
- 99. WEEE Directive ([download](#))



8007352664616  
1 NR  
5.2x5.7x7.6 [cm]  
69.2 [g]



8007352664623  
5 NR  
21.4x11.6x6 [cm]  
400.8 [g]



8007352726055  
50 NR  
30.5x25.5x22.5 [cm]  
4,008 [g]