



## NEVE UP: Dial thermostat 100-240V 2M carbon m

### 09470.CM

Wiring devices / Traditional wiring devices / NEVE UP / Devices

#### Dial thermostat 100-240V 2M carbon m

Dial thermostat with relay output 5(2) A 240 V~, heating and air conditioning in ON/OFF mode, class I temperature control device (contribution 1%), white LED backlighting with brightness control, 100-240 V 50/60 Hz power supply, carbon matt - 2 modules



3 - Active


1 NR



09026.PLS.CM - Button 1M +diffuser PLS symb. carbon matt




09026.DND.CM - Button 1M +diffuser DND symb. carbon matt




09290.CM - Shaver supply unit 230V carbon matt



09463.CM - Vertical badge switch 2M carbon matt



09465.CM - Vertical pocket badge switch carbon matt



09257.CM - 2P+E13ASICURY multistandard outlet carbon matt






09052.CM - 1P NO 10A cord-operated push carbon matt



09181.CM - IR relay-switch 230V carbon matt

- [Light Multilanguage instructions sheet \(516 kb\)](#)
- [Full multilanguage instructions sheet \(947 kb\)](#)




3D

- **Class group:** Stats, switches and controllers
- **Class:** Room thermostat
- **Differential value:** 0,00 - 1,00 k
- **Temperature readable:** No
- **Mounting method:** Flush-mounted

- **Max. contact voltage:** 230 V
- **Colour:** Anthracite
- **Height:** 47,00 mm
- **Width:** 44,80 mm
- **Depth:** 41,50 mm

- 00. CE Marking - EU
- 37. Marking - Morocco

- 43. UKCA mark - Great Britain
- 99. WEEE Directive ([download](#))



8007352667204  
1 NR  
5.7x5.3x7.7 [cm]  
78.6 [g]



8007352746527  
60 NR  
37.5x30x13.5 [cm]  
5,038.26 [g]



8007352667211  
70 NR  
39.5x30x17 [cm]  
5,878 [g]