



PLANA: 1P 10AX 2-way switch mechanism

14004.0

Wiring devices / Traditional wiring devices / PLANA / Devices

1P 10AX 2-way switch mechanism

1P 10 AX 250 V~ 2-way switch mechanism, lightable, to complete with 1,2 or 3-module button. Max 100 W for self-ballasted lamps (IEC 60669-1:2017)

3 - Active

50 NR





14021 - Button 1M lightable ring pilot white



14021.C - Button 1M bell symbol white



14021.C.SL - Button 1M bell symbol Silver



14021.G - Button 1M lightable disc pilot white



14021.G.SL - Button 1M customizable Silver



14021.L - Button 1M light symbol white



14021.L.SL - Button 1M light symbol Silver



14021.P - Button 1M key symbol white



14021.P.SL - Button 1M key symbol Silver



14021.PS - Button 1M PRESS white



14021.PS.SL - Button 1M PRESS Silver



14021.SL - Button 1M lightable Silver



14022 - Button 2M lightable ring pilot white



14022.AB - Antibacterial Button 2M lightable



14022.C - Button 2M bell symbol white



14022.C.SL - Button 2M bell symbol Silver



14022.G - Button 2M lightable disc pilot white



14022.G.SL - Button 2M customizable Silver



14022.L - Button 2M light symbol white



14022.L.SL - Button 2M light symbol Silver



14022.P - Button 2M key symbol white



14022.P.SL - Button 2M key symbol Silver



14022.PS - Button 2M PRESS white



14022.PS.SL - Button 2M PRESS Silver



14022.SL - Button 2M lightable Silver



14023 - Button 3M lightable ring pilot white



14023.C - Button 3M bell symbol white



14023.C.SL - Button 3M bell symbol Silver



14023.G - Button 3M lightable disc pilot white



14023.G.SL - Button 3M customizable Silver



14023.SL - Button 3M lightable Silver



00931 - Pre-wired LED unit 110-250V 0,5W amber



00935.A - LED unit 12-24V 0,1W amber



00935.B - LED unit 12-24V 0,1W light blue



00935.G - LED unit 12-24V 0,1W green



00935.R - LED unit 12-24V 0,1W red



00935.W - LED unit 12-24V 0,1W white



00936.250.A - LED unit 250V 0,35W amber



00936.250.B - LED unit 250V 0,35W light blue






00936.250.G - LED unit 250V 0,35W green



00936.250.R - LED unit 250V 0,35W red



00936.250.W - LED unit 250V 0,35W white



3D

- **Class group:** Domestic switching devices
- **Class:** Installation switch
- **Wiring system:** Two-way switch
- **Method of operation:** Rocker/button
- **Assembly arrangement:** Modular device for domestic switching devices
- **Number of modules (module system):** 1
- **Push button switch:** Yes
- **Number of rockers:** 1
- **Mounting method:** Flush-mounted
- **Type of fastening:** Engage (snap)
- **With mounting plate:** No
- **Material:** Plastic
- **Material quality:** Thermoplastic
- **Halogen free:** Yes
- **Surface protection:** Untreated
- **Surface finishing:** Glossy
- **Colour:** Green
- **RAL-number (similar):** 9003
- **Label space/information surface:** Yes
- **Illumination:** Optional
- **Function lighting:** Control and orientation
- **Type of lighting:** LED exchangeable
- **Suitable for degree of protection (IP):** IP40
- **Nominal voltage:** 250 V
- **Rated current:** 10,00 A
- **Feedback-signal contact:** No
- **Connection type:** Screwed terminal
- **Washing machine switch:** No
- **Device width:** 22,30 mm
- **Device height:** 49,00 mm
- **Device depth:** 38,40 mm
- **Built-in depth:** 24,00 mm

- 00. CE Marking - EU
- 01. IMQ - Italy ([download](#))
- 10. EAC Eurasian Customs Union
- 14. TSE - Turkey
- 15. CCC - China ([download](#))
- 19. NOM - Mexico
- 20. IQC - Argentina
- 28. NSW - Australia ([download](#))
- 29. QCERT - Colombia
- 37. Marking - Morocco
- 43. UKCA mark - Great Britain
- 96. Electrotechnical expert ([download](#))
- 99. WEEE Directive ([download](#))



8 007352 106420
1 NR
4.1x2.8x5.3 [cm]
25.4 [g]



8007352118690
50 NR
21.6x11.6x14.3 [cm]
1,363.6 [g]



8007352641006
500 NR
57.5x22.5x30 [cm]
14,120 [g]