



## PLANA: IoT connected radar sensor 1M white

---

**14179**

Wiring devices / View Wireless wiring devices / PLANA / Devices



### IoT connected radar sensor 1M white

3 - Active

1 NR



- [Light Multilanguage instructions sheet \(1346 kb\)](#)
- [Foglio istruzioni Full \(1138 kb\)](#)
- [Feuille d'instructions Full \(1139 kb\)](#)
- [Hoja de instrucciones Full \(1138 kb\)](#)
- [Full Instructions sheet \(1135 kb\)](#)
- [Φυλλάδιο οδηγιών Full \(1219 kb\)](#)
- [Anweisungsblatt Full \(1139 kb\)](#)
- [Full \(1219 kb\)](#)
- [Manuale app View Wireless \(15556 kb\)](#)
- [Manuel appli View Wireless \(37703 kb\)](#)
- [Manual app View Wireless \(37528 kb\)](#)
- [Manual View Wireless app \(37579 kb\)](#)
- [Εγχειρίδιο τεχνικού εγκατάστασης \(37781 kb\)](#)
- [Installationsanleitung View Wireless \(37508 kb\)](#)



3D

- **Class group:** Domestic switching devices
- **Class:** Movement sensor/presence detector complete
- **Model:** Movement sensor
- **Sensor type:** High frequency
- **With DALI interface:** No
- **Constant light control:** No
- **HVAC-control:** No
- **Forced switch on:** Yes
- **Forced switch off:** No
- **Animal zone:** Yes
- **Creep-under protection:** No
- **Networkable:** Yes
- **Scan angle:** 100
- **Staircase light controller:** No
- **Bridging switch:** No
- **Max. reach frontally:** 7 m
- **Suitable for wireless transmission:** Yes
- **Remote operation:** Yes
- **With remote control:** No
- **Response value sensitivity adjustable:** Yes
- **With signal unit:** Yes
- **Teach-function for response value luminosity:** No
- **Dim function with dimmer basic element:** No
- **Mounting method:** Flush-mounted
- **Suitable for ceiling mounting:** No
- **Connection type:** Screwed terminal
- **Material:** Plastic
- **Material quality:** Thermoplastic
- **Halogen free:** Yes
- **Surface protection:** Untreated
- **Surface finishing:** Glossy
- **Anti-bacterial treatment:** No
- **Colour:** White
- **RAL-number (similar):** 9003
- **Transparent:** No
- **Degree of protection (IP):** IP40
- **Voltage type:** AC
- **Frequency:** 50 - 60 HZ
- **Min. switch-on time:** 70 s
- **Switch-off delay:** 1.080 s
- **Detection angle horizontal:** 0 - 100
- **Max. switching power:** 960,00 W
- **Temperature:** 10 - 40 °C
- **Number of switching zones:** 1
- **Min. starting current:** 0 A
- **Substation input:** No
- **With alarm function:** Yes
- **Width:** 2.230,00 mm
- **Height:** 49,00 mm
- **Depth:** 4.950,00 mm
- **Diameter:** 0,00 mm
- **Built-in depth:** 3.900,00 mm
- **Built-in diameter:** 0,00 mm
- **Compatible with Apple HomeKit:** Yes
- **Compatible with Google Assistant:** Yes
- **Compatible with Amazon Alexa:** Yes

- 00. CE Marking - EU
- 00. CE Marking - EU
- 01. IMQ - Italy ([download](#))
- 37. Marking - Morocco
- 40. Bluetooth technology

- 43. UKCA mark - Great Britain
- 92. RoHS UAE
- 96. Electrotechnical expert ([download](#))
- 99. WEEE Directive ([download](#))



8007352709294  
1 NR  
6x5.4x5.2 [cm]  
46.8 [g]



8007352709300  
10 NR  
28.1x13.1x6 [cm]  
542.8 [g]

Vimar