



PLANA: TV-RD-SAT through-line outlet 2outs Silv

14302.10.SL

Wiring devices / Traditional wiring devices / PLANA / Devices




TV-RD-SAT through-line outlet 2outs Silv

Coaxial TV-RD-SAT 5-2400 MHz socket outlet, through-line, demix, 2 outputs with male (TV-RD) and female F-type (SAT) connectors, connection attenuation 10 dB, Silver - 2 modules

3 - Active

10 NR

- [Multilanguage instructions sheet \(905 kb\)](#)



3D

- **Class group:** Antenna and satellite technique
- **Class:** Antenna socket box
- **Model:** TWIN end socket
- **Cover:** None
- **Tap loss at 860 MHz:** 11,20 dB
- **Tap loss at 2150 MHz:** 12,00 dB
- **Number of outlets:** 2
- **Through loss at 860 MHz:** 2,00 dB

- **Through loss at 2150 MHz:** 2,80 dB
- **Suitable for remote power supply:** No
- **Type of fastening:** Snap mounting (engagement)
- **Colour:** Silver
- **RAL-number (similar):** 9006
- **Surface protection:** Lacquered
- **Material:** Plastic

- 00. CE Marking - EU
- 10. EAC Eurasian Customs Union
- 37. Marking - Morocco

- 43. UKCA mark - Great Britain
- 99. WEEE Directive ([download](#))



8 007352400832
 1 NR
 5.1x4.3x5.3 [cm]
 80.8 [g]



8 007352400993
 10 NR
 26.9x11.6x4.9 [cm]
 872.6 [g]

Vimar