



IDEA: TV-RD-SAT through-line.out.2outs white

16307.10.B

Wiring devices / Traditional wiring devices / IDEA / Devices




TV-RD-SAT through-line.out.2outs white

Coaxial TV-RD-SAT 5-2400 MHz socket outlet, through-line, demix, 2 outputs with male (TV-RD) and female F-type (SAT) connectors, connection attenuation 10 dB, white - 2 modules

2 - Will be discontinued

10 NR

- [Multilanguage instructions sheet \(905 kb\)](#)



3D

- **Class group:** Antenna and satellite technique
- **Class:** Antenna socket box
- **Model:** TWIN end socket
- **Cover:** None
- **Tap loss at 860 MHz:** 11,20 dB
- **Tap loss at 2150 MHz:** 12,00 dB
- **Number of outlets:** 2

- **Through loss at 860 MHz:** 2,00 dB
- **Through loss at 2150 MHz:** 2,80 dB
- **Suitable for remote power supply:** No
- **Type of fastening:** Snap mounting (engagement)
- **Colour:** White
- **RAL-number (similar):** 9001
- **Material:** Plastic

- 00. CE Marking - EU
- 37. Marking - Morocco

- 99. WEEE Directive ([download](#))



8007352400870
1 NR
5.1x4.3x5.3 [cm]
84.9 [g]



8007352401037
10 NR
26.9x11.6x4.9 [cm]
901.8 [g]

Vimar