



IDEA: Vertical badge switch white

16465.B

Wiring devices / Traditional wiring devices / IDEA / Devices

Vertical badge switch white

Electronic badge switch with vertical pocket, 16 A 250 V~ change-over relay output, supply voltage 230 V~ 50-60 Hz, 24 V~ 50-60 Hz and 24 Vd.c. (SELV), white - 3 modules. Provided without ISO card (badge)






3 - Active

1 NR



16452.S - ISO card

- [Light Multilanguage instructions sheet \(749 kb\)](#)
- [Full Multilanguage instructions sheet \(816 kb\)](#)



3D

- **Class group:** Alarm installations, emergency call and signalling
- **Class:** Access control system
- **Standalone:** Yes
- **Networkable:** No
- **PC-binding:** No
- **Type of interface:** None
- **Reading strategy:** Data medium
- **Signalling:** None
- **Mounting method:** Flush-mounted
- **Operating voltage AC 50 Hz:** 250,00 - 250,01 V
- **Operating voltage AC 60 Hz:** 250,00 - 250,01 V
- **Operating temperature:** 5 - 45 °C
- **Degree of protection (IP):** IP20
- **Colour:** White
- **Material:** Plastic
- **Width:** 74,80 mm
- **Height:** 50,10 mm
- **Depth:** 49,20 mm

- 00. CE Marking - EU
- 37. Marking - Morocco
- 37. Marking - Morocco
- 43. UKCA mark - Great Britain
- 96. Electrotechnical expert ([download](#))
- 99. WEEE Directive ([download](#))



8 007352301993

8007352301993
1 NR
5.7x5.3x7.7 [cm]
167 [g]



8 007352738416

8007352738416
5 NR
21.4x11.6x6 [cm]
891.8 [g]



8 007352738423

8007352738423
50 NR
30.5x25.5x22.5 [cm]
9,258 [g]