



## IDEA: Connected actuator 16A grey

---

**16493**

Wiring devices / View Wireless wiring devices / IDEA / Devices

### **Connected actuator 16A grey**

View Wireless electronic control device with NO 16 A 100-240 V~ 50/60 Hz relay output, local control with push button or remote control, double IoT technology on Bluetooth 5.0 standard for the creation of View Wireless mesh system and on Zigbee 3.0 standard, function for measuring the instant power and energy consumed and load cut-off threshold, RGB LED visible in darkness with brightness control, 100-240 V 50/60 Hz power supply, grey

- Configuration from View Wireless App for Bluetooth technology system and Amazon App for Zigbee technology
- Compatible with Alexa, Google Home and IFTTT, using the dedicated gateway or Zigbee hub
- Compatible with SmartThings hub






3 - Active

1 NR

- Light Multilanguage instructions sheet (1031 kb)
- Foglio istruzioni Full (550 kb)
- Feuille d'instructions Full (548 kb)
- Hoja de instrucciones Full (546 kb)
- Full instructions sheet (544 kb)
- Φυλλάδιο οδηγιών Full (720 kb)
- Anweisungsblatt Full (547 kb)
- Full (610 kb)
- Manuale app View Wireless (15556 kb)
- Manuel appli View Wireless (37703 kb)
- Manual app View Wireless (37528 kb)
- Manual View Wireless app (37579 kb)
- Εγχειρίδιο τεχνικού εγκατάστασης (37781 kb)
- Installationsanleitung View Wireless (37508 kb)

- Creating-the-system
- Customisations
- Operation-in-Zigbee-mode
- Bluetooth-wifi-gateway



3D



- **Class group:** Installation bus systems
- **Class:** Switch actuator for bus system
- **Bus system KNX:** No
- **Bus system KNX-RF (Radio Frequent):** No
- **Bus system radio frequent:** Yes
- **Bus system LON:** No
- **Bus system Powernet:** No
- **Other bus systems:** None
- **Radio frequent bidirectional:** Yes
- **Mounting method:** Flush-mounted
- **Width in number of modular spacings:** 1

- **Local operation/hand operation:** Yes
- **With LED indication:** Yes
- **Suitable for C-load:** Yes
- **Max. number of switching contacts:** 1
- **Rated current:** 16 A
- **Rated operating voltage:** 230,00 - 230,01 V
- **Different phases connectable:** No
- **With bus connection:** Yes
- **Modular expandability:** No
- **Degree of protection (IP):** IP40

- 00. CE Marking - EU
- 01. IMQ - Italy ([download](#))
- 19. NOM - Mexico

- 42. Zigbee certified
- 43. UKCA mark - Great Britain
- 99. WEEE Directive ([download](#))



8007352642980  
1 NR  
6x5.4x5.2 [cm]  
59.8 [g]



8007352649873  
60 NR  
37.5x30x13.5 [cm]  
3,930 [g]