



## IDEA: Connected roller shutter actuator white

---

### 16494.B

Wiring devices / View Wireless wiring devices / IDEA / Devices

#### Connected roller shutter actuator white

View Wireless electronic control for 1 roller shutter with slat orientation and change-over relay output for cosφ 0.6 motor 2 A 100-240 V~ 50/60 Hz, local or remote control, double IoT technology on Bluetooth 5.0 standard for the creation of View Wireless mesh system and on Zigbee 3.0 standard, 1 input for external push button to recall a scenario, favourite position recall function, RGB LED visible in darkness with brightness control, 100-240 V 50/60 Hz power supply, white

- Configuration from View Wireless App for Bluetooth technology system and Amazon App for Zigbee technology
- Compatible with Alexa, Google Home and IFTTT, using the dedicated gateway or Zigbee hub
- Compatible with SmartThings hub






3 - Active

1 NR

- Light multilanguage instructions sheet (940 kb)
- Foglio istruzioni Full (508 kb)
- Feuille d'instructions Full (509 kb)
- Hoja de instrucciones Full (507 kb)
- Full instructions sheet (504 kb)
- Φυλλάδιο οδηγιών Full (653 kb)
- Anweisungsblatt Full (776 kb)
- Full (575 kb)
- Manuale app View Wireless (15556 kb)
- Manuel appli View Wireless (37703 kb)
- Manual app View Wireless (37528 kb)
- Manual View Wireless app (37579 kb)
- Εγχειρίδιο τεχνικού εγκατάστασης (37781 kb)
- Installationsanleitung View Wireless (37508 kb)

- Creating-the-system
- Customisations
- Operation-in-Zigbee-mode
- Bluetooth-wifi-gateway



3D

- **Class group:** Domestic switching devices
- **Class:** Push button
- **Assembly arrangement:** Modular device for domestic switching devices
- **Model:** Group push button
- **Method of operation:** Push button
- **Number of rockers:** 2
- **Number of modules (module system):** 100
- **Number of poles:** 1
- **Nominal voltage:** 230 V
- **Rated current:** 2,00 A
- **With lighting:** Yes
- **With signal lamp:** Yes
- **Feedback-signal contact:** No
- **Mounting method:** Flush-mounted

- **Type of fastening:** Engage (snap)
- **Material:** Plastic
- **Material quality:** Thermoplastic
- **Anti-bacterial treatment:** No
- **Surface protection:** Untreated
- **Surface finishing:** Matt
- **Colour:** White
- **RAL-number (similar):** 9001
- **Transparent:** No
- **Label space/information surface:** Yes
- **Imprint:** Other
- **Device width:** 22,30 mm
- **Device height:** 49,00 mm
- **Device depth:** 46,40 mm

- 00. CE Marking - EU
- 01. IMQ - Italy ([download](#))
- 37. Marking - Morocco
- 40. Bluetooth technology

- 42. Zigbee certified
- 43. UKCA mark - Great Britain
- 46. UK PSTI compliance ([download](#))
- 99. WEEE Directive ([download](#))



8007352642997  
1 NR  
5.2x3.5x5.3 [cm]  
56.6 [g]



8007352649507  
60 NR  
27x23x12.5 [cm]  
3,710 [g]

Vimar