



Connector block boxes: Flush mounting box for panel mounting

16776.AU


System infrastructure / Enclosures and control units / Connector block boxes / Flush mounting

Flush mounting box for panel mounting

Flush mounting box for panel mounting frames (GW 960 °C), black

3 - Active

12 NR







Class group: Connection material (electrotechnical)

Class: Box/housing for built-in mounting in the wall/ceiling

Mounting method: Other

Shape: Rectangular

Construction type: Device connection box (round/square)

Model: Single

Provided with revolving ring: No

• Couplable: No

Equipped with: None
Diameter: 25 mm
Length: 54,00 mm
Width: 29,00 mm
Depth: 0,00 - 42,20 mm

Inner depth: 36,20 mm

For number of electric fittings: 1

Mounting switching equipment: Spread

With screws: No

Housing feed-through by break-out opening: Yes

Housing feed-through by seal membrane: No

Housing feed-through by nozzle: No

Housing feed-through by step membrane: No

• For tube diameter: 20/25 mm

Suitable for cable diameter: 0 - 25 mm

Pipe locking: No

Pipe locking optional: No Inlet from the rear: Yes

Number of inlets: 3

Number of included spouts: 0

Material: Plastic Halogen free: Yes

Surface protection: Untreated

Colour: Black

Degree of protection (IP): IP40

Cover model: NoneTransparent cover: NoCover attachment: Other

Sealable: No

With screening: No

Air tight: No

Max. conductor cross section: 0Number of poles of the clamp: 0

Clamp position fixed: No

Luminaire hook mounting: No

Nozzle: None

Special application: None

01. IMQ - Italy (download)

• 15. CCC - China (download)

96. Electrotechnical expert (download)



8007352082496 1 NR 2.9x5.4x4.2 [cm] 9.6 [g]



8007352084094 12 NR 14.2x9.8x9.1 [cm] 159.93 [g]

Vimar