



## IDEA: TV-RD-SAT single conn.male outlet 1dB w

### 17066.01.B




Wiring devices / Traditional wiring devices / IDEA / Devices

#### TV-RD-SAT single conn.male outlet 1dB w

Coaxial TV-RD-SAT 5-2400 MHz socket outlet, single connection, with IEC 60169-2 male connector, connection attenuation 1 dB, white - reduced module. Allows the passage of d.c. current and control signals (24 V 500 mA max).

3 - Active

20 NR



3D

- **Class group:** Antenna and satellite technique
- **Class:** Antenna socket box
- **Model:** End socket
- **Cover:** None
- **Tap loss at 860 MHz:** 0,10 dB
- **Tap loss at 2150 MHz:** 0,20 dB

- **Number of outlets:** 1
- **Suitable for remote power supply:** Yes
- **Type of fastening:** Snap mounting (engagement)
- **Colour:** White
- **RAL-number (similar):** 9001
- **Material:** Plastic

- 00. CE Marking - EU
- 10. EAC Eurasian Customs Union
- 37. Marking - Morocco

- 43. UKCA mark - Great Britain
- 99. WEEE Directive ([download](#))



8007352011557  
1 NR  
4.1x2.8x5.3 [cm]  
41.2 [g]



8007352013841  
20 NR  
21.4x11.6x6 [cm]  
881 [g]

Vimar