



IDEA: TV-RD-SAT single-conn.out.2outs white

17067.01.B

Wiring devices / Traditional wiring devices / IDEA / Devices

TV-RD-SAT single-conn.out.2outs white




Coaxial TV-RD-SAT 5-2400 MHz socket outlet, single connection, demix, 2 outputs with male (TV-RD) and female F-type (SAT) connectors, connection attenuation 1 dB, white - 2 reduced modules. Allows the passage of d.c. current and control signals (24 V 500 mA max) through the female connector



3 - Active

10 NR

- [Multilanguage instructions sheet \(905 kb\)](#)



3D

- **Class group:** Antenna and satellite technique
- **Class:** Antenna socket box
- **Model:** TWIN end socket
- **Cover:** None
- **Tap loss at 860 MHz:** 1,00 dB
- **Tap loss at 2150 MHz:** 1,00 dB

- 00. CE Marking - EU
- 10. EAC Eurasian Customs Union
- 37. Marking - Morocco

- **Number of outlets:** 2
- **Suitable for remote power supply:** Yes
- **Type of fastening:** Snap mounting (engagement)
- **Colour:** White
- **RAL-number (similar):** 9001
- **Material:** Plastic

- 43. UKCA mark - Great Britain
- 99. WEEE Directive ([download](#))



8007352400894
1 NR
5.1x4.3x5.3 [cm]
83.3 [g]



8007352401051
10 NR
26.9x11.6x4.9 [cm]
885.8 [g]

Vimar