



ARKÉ: 2P 20AX 1-way switch 2M Metal

19016.2.M

Wiring devices / Traditional wiring devices / ARKÉ / Devices





2P 20AX 1-way switch 2M Metal

2P 20 AX 250 V~ 1-way switch, lightable, replaceable button, Metal - 2 modules. Max 250 W for self-ballasted lamps (IEC 60669-1:2017)

3 - Active

20 NR

- [Arké lives in your time](#)



3D

- **Class group:** Domestic switching devices
- **Class:** Installation switch
- **Wiring system:** 2-pole switch
- **Method of operation:** Rocker/button
- **Assembly arrangement:** Modular device for domestic switching devices
- **Number of modules (module system):** 2
- **Push button switch:** Yes
- **Number of rockers:** 1
- **Mounting method:** Flush-mounted
- **Type of fastening:** Engage (snap)
- **With mounting plate:** No
- **Material:** Plastic
- **Material quality:** Thermoplastic
- **Halogen free:** Yes
- **Surface protection:** Lacquered
- **Surface finishing:** Matt

- **Colour:** Aluminium
- **RAL-number (similar):** 9007
- **Label space/information surface:** Yes
- **Illumination:** Optional
- **Function lighting:** Control and orientation
- **Type of lighting:** LED exchangeable
- **Suitable for degree of protection (IP):** IP40
- **Nominal voltage:** 250 V
- **Rated current:** 20,00 A
- **Feedback-signal contact:** No
- **Connection type:** Screwed terminal
- **Washing machine switch:** Yes
- **Device width:** 44,80 mm
- **Device height:** 49,00 mm
- **Device depth:** 37,10 mm
- **Built-in depth:** 26,00 mm

- 00. CE Marking - EU
- 01. IMQ - Italy ([download](#))
- 36. ISI - India
- 37. Marking - Morocco

- 43. UKCA mark - Great Britain
- 92. RoHS UAE
- 96. Electrotechnical expert ([download](#))
- 99. WEEE Directive ([download](#))



8007352598751
1 NR
5.1x4.3x5.3 [cm]
40.8 [g]



8007352598768
20 NR
26.9x11.6x9 [cm]
898.2 [g]

Vimar