



ARKÉ: 2P 16AX 1-way sw.+000-key grey

19083.CU

Wiring devices / Traditional wiring devices / ARKÉ / Devices




2P 16AX 1-way sw.+000-key grey

2P 16 AX 250 V~ key-operated 1-way switch, 000 unified key removable in both positions, grey. Max 200 W for self-ballasted lamps (IEC 60669-1:2017)

3 - Active

20 NR

- [Arké lives in your time](#)



3D



- **Class group:** Domestic switching devices
- **Class:** Installation switch
- **Wiring system:** 2-pole switch
- **Method of operation:** Key
- **Assembly arrangement:** Other
- **Number of modules (module system):** 1
- **Push button switch:** Yes
- **Number of rockers:** 0
- **Mounting method:** Flush-mounted
- **Type of fastening:** Engage (snap)
- **With mounting plate:** No
- **Material:** Plastic
- **Material quality:** Thermoplastic
- **Halogen free:** Yes
- **Surface protection:** Untreated
- **Surface finishing:** Matt
- **Colour:** Grey
- **RAL-number (similar):** 7015
- **Label space/information surface:** Yes
- **Illumination:** No
- **Function lighting:** Other
- **Type of lighting:** Other
- **Suitable for degree of protection (IP):** IP40
- **Nominal voltage:** 250 V
- **Rated current:** 16,00 A
- **Feedback-signal contact:** No
- **Connection type:** Screwed terminal
- **Washing machine switch:** Yes
- **Device width:** 22,30 mm
- **Device height:** 49,00 mm
- **Device depth:** 43,50 mm
- **Built-in depth:** 33,00 mm
- 00. CE Marking - EU
- 10. EAC Eurasian Customs Union
- 14. TSE - Turkey ([download](#))
- 29. QCERT - Colombia
- 37. Marking - Morocco
- 43. UKCA mark - Great Britain
- 96. Electrotechnical expert ([download](#))
- 99. WEEE Directive ([download](#))



8 007352414082

8007352414082
1 NR
5.1x2.8x5.3 [cm]
55.2 [g]



8 007352414099

8007352414099
20 NR
27x11.6x6 [cm]
1,173 [g]

Vimar