



## ARKÉ: 2P+E 16A German SICURY outlet+cover w

### 19208.C.B

Wiring devices / Traditional wiring devices / ARKÉ / Devices




### 2P+E 16A German SICURY outlet+cover w

2P+E 16 A 250 V~ SICURY socket outlet, German standard, with cover, white -  
2 modules

3 - Active

10 NR

- [Arké lives in your time](#)



3D

- **Class group:** Domestic switching devices
- **Class:** Socket outlet
- **Number of units:** 1
- **Number of modules (module system):** 2
- **Number of socket outlets switchable:** 0
- **Imprint/indication:** None
- **Connection type:** Screwed terminal
- **With hinged lid:** Yes
- **With enhanced contact protection:** Yes
- **Label space/information surface:** Yes
- **Colour:** White
- **RAL-number (similar):** 9016
- **Metallic colour:** No
- **Transparent:** No
- **Lockable:** No
- **Eject-mechanism:** No
- **Insulated mounting:** No
- **With function lighting:** Yes
- **With orientation lighting:** No

- 00. CE Marking - EU
- 09. VDE - Germany ([download](#))
- 10. EAC Eurasian Customs Union
- 12. AENOR - Spain ([download](#))

- **Over voltage protection:** No
- **Fault current protection:** No
- **Mounting method:** Flush-mounted
- **Material:** Plastic
- **Material quality:** Thermoplastic
- **Halogen free:** Yes
- **Surface protection:** Untreated
- **Surface finishing:** Matt
- **With loop through function:** No
- **With on/off switch:** No
- **Rotated central insert:** No
- **Nominal current:** 16 A
- **Nominal voltage:** 250 V
- **Frequency:** 50,00 - 60,00 HZ
- **Suitable for degree of protection (IP):** IP20
- **Impact strength:** Other
- **Device width:** 44,80 mm
- **Device height:** 49,00 mm
- **Device depth:** 38,90 mm

- 13. SNI - Indonesia
- 14. TSE - Turkey
- 37. Marking - Morocco
- 99. WEEE Directive ([download](#))



8007352474550  
1 NR  
5.1x4.3x5.3 [cm]  
53 [g]



8007352474567  
10 NR  
26.9x11.6x4.9 [cm]  
595 [g]