



ARKÉ: 2P+E 16A USA+EU SICURY outlet white

19248.B

Wiring devices / Traditional wiring devices / ARKÉ / Devices




2P+E 16A USA+EU SICURY outlet white

2P+E 16 A 250 V~ SICURY socket outlet, polarized Euro-American standard, white - 2 modules

3 - Active

20 NR

- [Arké lives in your time](#)



3D

- **Class group:** Domestic switching devices
- **Class:** Socket outlet
- **Model:** Other
- **Number of units:** 1
- **Number of modules (module system):** 2
- **Number of socket outlets switchable:** 0
- **Imprint/indication:** None
- **Connection type:** Screwed terminal
- **With hinged lid:** No
- **With enhanced contact protection:** Yes
- **Label space/information surface:** Yes
- **Colour:** White
- **RAL-number (similar):** 9016
- **Metallic colour:** No
- **Transparent:** No
- **Lockable:** No
- **Eject-mechanism:** No
- **Insulated mounting:** No
- **With function lighting:** No
- **With orientation lighting:** No

- 00. CE Marking - EU
- 00. CE Marking - EU
- 10. EAC Eurasian Customs Union
- 29. QCERT - Colombia ([download](#))

- **Over voltage protection:** No
- **Fault current protection:** No
- **Mounting method:** Flush-mounted
- **Material:** Plastic
- **Material quality:** Thermoplastic
- **Halogen free:** Yes
- **Surface protection:** Untreated
- **Surface finishing:** Matt
- **With loop through function:** No
- **With on/off switch:** No
- **Rotated central insert:** No
- **Nominal current:** 16 A
- **Nominal voltage:** 250 V
- **Frequency:** 50,00 - 60,00 HZ
- **Suitable for degree of protection (IP):** IP20
- **Impact strength:** Other
- **Device width:** 44,80 mm
- **Device height:** 49,00 mm
- **Device depth:** 36,00 mm

- 37. Marking - Morocco
- 96. Electrotechnical expert ([download](#))
- 99. WEEE Directive ([download](#))



8007352474802
1 NR
5.1x4.3x5.3 [cm]
44.8 [g]



8007352474819
20 NR
26.9x11.6x9 [cm]
978.2 [g]