




## ARKÉ: TV-RD-SAT single-conn.out.2outs grey

**19302.01**

Wiring devices / Traditional wiring devices / ARKÉ / Devices

### TV-RD-SAT single-conn.out.2outs grey

Coaxial TV-RD-SAT 5-2400 MHz socket outlet, single connection, demix, 2 outputs with male (TV-RD) and female F-type (SAT) connectors, connection attenuation 1 dB, grey - 2 modules. Allows the passage of d.c. current and control signals (24 V 500 mA max) through the female connector






3 - Active

10 NR

• [Multilanguage instructions sheet \(905 kb\)](#)

• [Arké lives in your time](#)



3D



- **Class group:** Antenna and satellite technique
- **Class:** Antenna socket box
- **Model:** TWIN end socket
- **Cover:** None
- **Tap loss at 860 MHz:** 1,00 dB
- **Tap loss at 2150 MHz:** 1,00 dB
- **Number of outlets:** 2

- **Suitable for remote power supply:** Yes
- **Type of fastening:** Snap mounting (engagement)
- **Colour:** Grey
- **RAL-number (similar):** 7015
- **Surface protection:** Untreated
- **Material:** Plastic

- 00. CE Marking - EU
- 10. EAC Eurasian Customs Union
- 37. Marking - Morocco

- 43. UKCA mark - Great Britain
- 99. WEEE Directive ([download](#))



8007352414563  
1 NR  
5.1x4.3x5.3 [cm]  
79.5 [g]



8007352414570  
10 NR  
26.9x11.6x4.9 [cm]  
858.6 [g]



8007352654945  
200 NR  
47.5x27x29 [cm]  
17,980 [g]