



ARKÉ: 1P+N C6 10mA RCBO Metal

19411.06.M

Wiring devices / Traditional wiring devices / ARKÉ / Devices

1P+N C6 10mA RCBO Metal

1P+N C 6 residual current breaker with overcurrent protection, supply voltage 120-230 V~ 50-60 Hz, $I_{\Delta n}$ 10 mA, breaking capacity 1500 A, Metal - 2 modules




3 - Active

5 NR



- [Multilanguage instructions sheet \(688 kb\)](#)

- [Arké lives in your time](#)



3D

- **Class group:** Circuit breakers and fuses
- **Class:** Earth leakage circuit breaker
- **Number of poles (total):** 2
- **Number of protected poles:** 1
- **Rated voltage:** 230 V
- **Rated current:** 6 A
- **Rated fault current:** 6 A
- **Leakage current type:** A
- **Current limiting class:** 1
- **Rated short-circuit breaking capacity I_{cn} according to EN 61009-1:** 1,50 kA
- **Surge current capacity:** 1,50 kA
- **Voltage type:** AC
- **Frequency:** 50/60 Hz
- **Release characteristic:** C
- **Concurrently switching neutral conductor:** Yes
- **Over voltage category:** 3
- **Built-in depth:** 38,00 mm
- **Flush-mounted installation:** Yes
- **Anti- nuisance tripping version:** No
- **Degree of protection (IP):** IP40

- 00. CE Marking - EU
- 37. Marking - Morocco
- 96. Electrotechnical expert ([download](#))
- 99. WEEE Directive ([download](#))



8007352600768
1 NR
6x5.4x5.3 [cm]
97.5 [g]



8007352602328
5 NR
17.2x13.1x6 [cm]
547.1 [g]

Vimar