



ARKÉ: Vertical badge switch 2M antibact.white

19463.AB.B

Wiring devices / Traditional wiring devices / ARKÉ / Devices




Vertical badge switch 2M antibact.white

Upright electronic badge switch, 4 A 250 V~ NO (NON SELV) change-over relay output, power supply 120-230 V~ 50-60 Hz, slot lighting for location in the dark, trimmer for regulating switch-off time after removing the card, antibacterial material, white - 2 modules. Supplied without ISO card (badge)



3 - Active

1 NR



3D

- **Class group:** Alarm installations, emergency call and signalling
- **Class:** Access control system
- **Standalone:** Yes
- **Networkable:** No
- **PC-binding:** No
- **Type of interface:** None
- **Reading strategy:** Data medium
- **Signalling:** None
- **Mounting method:** Flush-mounted
- **Operating voltage AC 50 Hz:** 250,00 - 250,01 V

- **Operating voltage AC 60 Hz:** 250,00 - 250,01 V
- **Operating voltage DC:** 220,00 - 230,00 V
- **Operating temperature:** 5 - 35 °C
- **Degree of protection (IP):** IP20
- **Colour:** White
- **Model:** Other
- **Material:** Plastic
- **Width:** 44,80 mm
- **Height:** 49,00 mm
- **Depth:** 43,50 mm

- 00. CE Marking - EU
- 43. UKCA mark - Great Britain

- 99. WEEE Directive ([download](#))



8007352652668
1 NR
5.2x5.7x7.6 [cm]
68.5 [g]



8007352652675
5 NR
21.4x11.6x6 [cm]
399.3 [g]



8007352726116
50 NR
30.5x25.5x22.5 [cm]
3,993 [g]

Vimar